



At Sololuce , we believe the best lighting is found in the balance of Beauty and Control. This harmony is the soul of Sololuce and is the means by which we impart beauty and control to people's lives. To create warm shades, cool tones and rich comfort in a naturally adaptive way.


All accomplished with the most subtle and natural of mediums known... Light


LED Lighting


Sololuce LED Lighting


	Esplanda	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1101-36</td><td rowspan="2">Pressure die cast fixture in 36w and 72 w</td></tr><tr><td>LED 1101-72</td></tr></table>	Model No		LED 1101-36	Pressure die cast fixture in 36w and 72 w	LED 1101-72				
Model No											
LED 1101-36	Pressure die cast fixture in 36w and 72 w										
LED 1101-72											
	Modulo	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1104-40</td><td rowspan="6">Pressure die cast aluminum street luminaire available from 40w till 150w in adjustable and replaceable LED modules .</td></tr><tr><td>LED 1105-60</td></tr><tr><td>LED 1106-80</td></tr><tr><td>LED 1107-100</td></tr><tr><td>LED 1108-120</td></tr><tr><td>LED 1109-150</td></tr></table>	Model No		LED 1104-40	Pressure die cast aluminum street luminaire available from 40w till 150w in adjustable and replaceable LED modules .	LED 1105-60	LED 1106-80	LED 1107-100	LED 1108-120	LED 1109-150
Model No											
LED 1104-40	Pressure die cast aluminum street luminaire available from 40w till 150w in adjustable and replaceable LED modules .										
LED 1105-60											
LED 1106-80											
LED 1107-100											
LED 1108-120											
LED 1109-150											
	Leaf	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1645-26</td><td rowspan="3">Pressure die cast aluminum street luminaire contrasted against the curved diffuser. Translucent /Opal refractor minimize dayform mass available in 26w,58w & 92 w in two sizes</td></tr><tr><td>LED 1646-58</td></tr><tr><td>LED 1646-92</td></tr></table>	Model No		LED 1645-26	Pressure die cast aluminum street luminaire contrasted against the curved diffuser. Translucent /Opal refractor minimize dayform mass available in 26w,58w & 92 w in two sizes	LED 1646-58	LED 1646-92			
Model No											
LED 1645-26	Pressure die cast aluminum street luminaire contrasted against the curved diffuser. Translucent /Opal refractor minimize dayform mass available in 26w,58w & 92 w in two sizes										
LED 1646-58											
LED 1646-92											
	Urbano	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1102-27</td><td rowspan="2">Made of pressure die cast aluminum housing with pure silicon gaskets , ss hardware and powder coated externally. Luminaire is available in 27w and 60w Led .</td></tr><tr><td>LED 1102-60</td></tr></table>	Model No		LED 1102-27	Made of pressure die cast aluminum housing with pure silicon gaskets , ss hardware and powder coated externally. Luminaire is available in 27w and 60w Led .	LED 1102-60				
Model No											
LED 1102-27	Made of pressure die cast aluminum housing with pure silicon gaskets , ss hardware and powder coated externally. Luminaire is available in 27w and 60w Led .										
LED 1102-60											
	Fantasi	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1103-40</td><td rowspan="2">The Fantasi luminaire is distinguished by the formally matched unit of mounting and circular luminaire construction and their simplified form. Luminare is made of pressure die cast aluminum in 40w & 80w .</td></tr><tr><td>LED 1103-80</td></tr></table>	Model No		LED 1103-40	The Fantasi luminaire is distinguished by the formally matched unit of mounting and circular luminaire construction and their simplified form. Luminare is made of pressure die cast aluminum in 40w & 80w .	LED 1103-80				
Model No											
LED 1103-40	The Fantasi luminaire is distinguished by the formally matched unit of mounting and circular luminaire construction and their simplified form. Luminare is made of pressure die cast aluminum in 40w & 80w .										
LED 1103-80											
	StyLux	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1660-24</td><td rowspan="2">Stylux , a pressure die cast aluminum luninaire with IP65 protection class can be used as decorative Highbay as well as outdoor contemporary street luminaire . Stylux is available in 24w and 36w .</td></tr><tr><td>LED 1660-36</td></tr></table>	Model No		LED 1660-24	Stylux , a pressure die cast aluminum luninaire with IP65 protection class can be used as decorative Highbay as well as outdoor contemporary street luminaire . Stylux is available in 24w and 36w .	LED 1660-36				
Model No											
LED 1660-24	Stylux , a pressure die cast aluminum luninaire with IP65 protection class can be used as decorative Highbay as well as outdoor contemporary street luminaire . Stylux is available in 24w and 36w .										
LED 1660-36											


	SIRRUS	<p>Model No</p> <p>LED 1305-40 SIRRUS is made of die cast aluminum body with Polycarbonate vandal resistant lens. Thermally tested and suitable for 40w LED.</p>
	KRYPTON	<p>Model No</p> <p>LED 1306-40 KRYPTON is made in corrosion free die cast aluminium and vandal resistant PC , giving it superior durability. KRYPTON is available in 40w LED.</p>
	FOGO	<p>Model No</p> <p>LED 1201-05 FOGO is pressure die cast aluminum finned fixture , available in 5w and 18w led and in two sizes .</p> <p>LED 1202-18</p>
	FOGO PLUS	<p>Model No</p> <p>LED 1564-24 Made in pressure die cast aluminum body with IP66 ingress protection with pure silicon gaskets and stainless steel hardware .</p> <p>LED 1564-24 Luminaire comes in two optical options of 6 deg and 30 deg beam. with in 24w LED power .</p>
	PRIMUS	<p>Model No</p> <p>LED 1206-36 Made of pressure die cast aluminum housing with pure silicon gaskets and SS hardware , Fixture is with IP66 ingress protection in 36w and 72w in two sizes .</p> <p>LED 1207-72</p>
	PRIMUS PLUS	<p>Model No</p> <p>LED 1501-36A</p> <p>LED 1501-36B</p> <p>LED 1501-36C</p> <p>LED 1501-36D</p> <p>LED 1502-72A</p> <p>LED 1502-72B</p> <p>LED 1502-72C</p> <p>LED 1502-72D</p> <p>Specially designed highly thermally efficient PRIMUS PLUS is a beauty during the day and a wonder at night. PRIMUS PLUS is made to satisfy a wide array of lighting needs in parks, gardens, Facades and avenues. Made of pressure die cast aluminum housing with pure silicon gaskets and SS hardware , Fixture is with IP66 ingress protection in 36w and 72w in two sizes and with four beam optics of 15/30/45/ 7 60 degree.</p>


	Spot	Model No
		<div> <div> LED 1204-01/15 LED 1204-01/25 LED 1204-01/45 LED 1204-01/60 LED 1205-03/15 LED 1205-03/25 LED 1205-03/45 LED 1205-03/60 </div> <div> <p>Series of adjustable spotlights in 1w & 3W. Can be used both indoors and/or outdoors and are available in pre-treated die cast aluminium with a protection rating up to IP66. They are very easy to install in walls or ground with screws . Ideal for lighting plants, flowerbeds, small paths, doorways and signs.</p> <p>Luminaire is available in 15/25/45 & 60 degree beam and in two sizes .</p> </div> </div>


	Dot	Model No
		<div> <div>LED 1441-03 LED 1442-03 LED 1443-04 LED 1444-04</div> <div> <p>Adjustable spotlights in 3w & 4w. can be used both indoors and/or outdoors and are available in pre-treated die cast aluminium with a protection rating up to IP66.</p> <p>Made of pressure die cast & available in two shapes .</p> </div> </div>


	Pluto	Model No
		<div> <div> LED 1503-15A LED 1503-15B LED 1503-15C LED 1503-15D LED 1504-15A LED 1504-15B LED 1504-15C LED 1504-15D LED 1505-30A LED 1505-30B LED 1505-30C LED 1505-30D </div> <div> <p>Creating Landscapes, Enhancing Facade Details, Creating ambience or highlighting things of substance, Pluto has the power to accomplish its job worth mentioning. A set of three models designed around pressure die cast fixture in IP66 protection class available in 15w single head and 30w double head.</p> <p>Fixture is available as Ground Mount, 1000mm pole mount or twin head 2000mm pole mount.</p> </div> </div>


	Pluto Mini	Model No	
		LED 1565-3	Pluto Mini is an extensive selection of models, components and light sources that provide unrivalled flexibility for landscape /facade designers and architects, regardless of project size and lighting task. Made of die cast aluminum in IP66 protection available in different beam angles and wattages of 3w,6w & 10w . LEDs available in warm white or cool white.
		LED 1566-6	
		LED 1566-6	
		LED 1567-10	







	Light Lines	Model No	
		LED 1568-12	This luminaire ensemble cannot fail to impress with its low profile, slim-line design emphasised by its linear contours. Fixture is made of aluminum extrusion profiles with stainless steel/die cast brackets , pure silicon gaskets and ss hardware. Fixtures are well suited to withstand water splashes and available in 12w,24w,40w & 54w LED .
		LED 1569-24	
		LED 1570-40	
		LED 1571-54	

	PanaLux	Model No	
		LED 1601-35	An integral indoor luminaire with backlit LED, offers the maximum usable light output without glare. Made of galvanized painted sheet/aluminum extrusion profile,PMMA/Acrylic diffuser .PanaLux is available in 35w and 40w options
		LED 1602-40	






	PanaSlim	Model No	
		LED 1603-16	Luminaire body is made of aluminum extrusion and from diffuser is made of PMMA/ Acrylic with special optics to diffuse the light evenly. Luminaire supports side mount LEDs and is only 9.7mm height .
		LED 1604-40	
		LED 1605-71	


	Matrix	Model No	
		LED 1487-35	Matrix is a series of specially designed recessed luminaires consisting of a special LED profile, designed by Sololuce for this lighting concept. Luminaire is available in 35w, 40w and 60w LED in 3 sizes .
		LED 1488-40	
		LED 1489-60	


	Qulsar	Model No	
		LED 2104-36	Quisar is a beautifully designed recessed luminaire consisting of a special LED profile, designed by Sololuce, available in 36w in 600x600mm ceiling profile


	Anteras	<p>Model No</p> <p>LED 1474-30</p> <p>Anteras is as specisl application surface mount fixture in IP66 pro-tection class, made of aluminum extrusion profile and abs end caps in 30w LED .</p>
	Aura	<p>Model No</p> <p>LED 2101-09</p> <p>LED 2102-12</p> <p>LED 2103-15</p> <p>Aura downlights support specially designed optics known as the "POLARIZING PRISM" diffuser , made of pressure die cast alu-minum in 9w , 12 w, and 15w LED and in 6" , 7" & 8" diameter .</p>
	Orbik	<p>Model No</p> <p>LED 2105-07</p> <p>LED 2105-12</p> <p>LED 2106-12</p> <p>LED 2106-18</p> <p>LED 2107-18</p> <p>LED 2107-24</p> <p>Orbik luminiare body is made of die cast aluminum with low heat resistance , installation ring made of sheet steel and white pow-der coated. Seperate housing for LED driver, available in 7w 12w 18w & 24w LED</p>
	Cielos I	<p>Model No</p> <p>LED 1536-13</p> <p>Cielos I is an IP65 downlight which support specially designed LED array mounted on horizontal die cast finned heat sink with vacuum metalized aluminum reflector. The downlight is designed for 13w Led chip.</p>
	Cielos II	<p>Model No</p> <p>LED 1537-18</p> <p>Cielos II is an IP65 integral driver downlight which support spe-cially designed LED array mounted on horizontal die cast finned heat sink with vacuum metalized aluminum reflector. The downlight is designed for 18w Led chip.</p>
	Lumen	<p>Model No</p> <p>LED 2108-09</p> <p>LED 2108-18</p> <p>LED 2108-27</p> <p>LED 2109-28</p> <p>Lumen is a range of simple and discrete fittings, able to be installed in a multitude of situations, all the while generating maximum visual comfort. The dual adjustability of the body, the practical mechanical locks make Lumen an extremely flexible instrument. Fixture made of aluminum die cast in 9w/ 18w/ 27w and 28w LED.</p>


	Briton	<table><tr><th>Model No</th><th></th></tr><tr><td>LED 2110-09</td><td>Briton is a simple and discrete fittings, able to be installed in a multitude of situations, all the while generating maximum visual comfort. The dual adjustability of the body, the practical mechanical locks make Lumen an extremely flexible instrument. Fixture made of aluminum die cast in 9w LED.</td></tr></table>	Model No		LED 2110-09	Briton is a simple and discrete fittings, able to be installed in a multitude of situations, all the while generating maximum visual comfort. The dual adjustability of the body, the practical mechanical locks make Lumen an extremely flexible instrument. Fixture made of aluminum die cast in 9w LED.		
Model No								
LED 2110-09	Briton is a simple and discrete fittings, able to be installed in a multitude of situations, all the while generating maximum visual comfort. The dual adjustability of the body, the practical mechanical locks make Lumen an extremely flexible instrument. Fixture made of aluminum die cast in 9w LED.							
	Micros	<table><tr><th>Model No</th><th></th></tr><tr><td>LED 1530-07A</td><td rowspan="2">Micros downlight support specially designed LED array with vacuum metalized aluminum reflector. Downlight comes in two versions with IP20 and IP65 ingress protection. IP65 version is with front glass.</td></tr><tr><td>LED 1530-07B (IP65)</td></tr></table>	Model No		LED 1530-07A	Micros downlight support specially designed LED array with vacuum metalized aluminum reflector. Downlight comes in two versions with IP20 and IP65 ingress protection. IP65 version is with front glass.	LED 1530-07B (IP65)	
Model No								
LED 1530-07A	Micros downlight support specially designed LED array with vacuum metalized aluminum reflector. Downlight comes in two versions with IP20 and IP65 ingress protection. IP65 version is with front glass.							
LED 1530-07B (IP65)								
	Arcos	<table><tr><th>Model No</th><th></th></tr><tr><td>LED 1531-07</td><td>The downlight is designed for 7w Led chip in 3000K & 5600k CCT with >80 CRI and in 37 degree beam angle. Downlight comes in with IP20 ingress protection and is available in White, Black, Grey, Chrome and Satin Nickel finish.</td></tr></table>	Model No		LED 1531-07	The downlight is designed for 7w Led chip in 3000K & 5600k CCT with >80 CRI and in 37 degree beam angle. Downlight comes in with IP20 ingress protection and is available in White, Black, Grey, Chrome and Satin Nickel finish.		
Model No								
LED 1531-07	The downlight is designed for 7w Led chip in 3000K & 5600k CCT with >80 CRI and in 37 degree beam angle. Downlight comes in with IP20 ingress protection and is available in White, Black, Grey, Chrome and Satin Nickel finish.							
	Panos	<table><tr><th>Model No</th><th></th></tr><tr><td>LED 1532-10.5</td><td rowspan="2">The downlight is designed for 10.5w and 15w Led chip in 3000K , 4000k & 5000k CCT with >80 CRI and in 16 & 18 degree beam angle. Downlight comes in with IP20 ingress protection .</td></tr><tr><td>LED 1532-15</td></tr></table>	Model No		LED 1532-10.5	The downlight is designed for 10.5w and 15w Led chip in 3000K , 4000k & 5000k CCT with >80 CRI and in 16 & 18 degree beam angle. Downlight comes in with IP20 ingress protection .	LED 1532-15	
Model No								
LED 1532-10.5	The downlight is designed for 10.5w and 15w Led chip in 3000K , 4000k & 5000k CCT with >80 CRI and in 16 & 18 degree beam angle. Downlight comes in with IP20 ingress protection .							
LED 1532-15								
	Credos	<table><tr><th>Model No</th><th></th></tr><tr><td>LED 1534-10.5</td><td rowspan="3">The downlight is designed in 10.5w/15w and 26w Led chip in 3000K & 5600k CCT with >80 CRI and in 16, 18 & 20 degree beam angle. Downlight comes in with IP20 ingress protection</td></tr><tr><td>LED 1534-15</td></tr><tr><td>LED 1534-26</td></tr></table>	Model No		LED 1534-10.5	The downlight is designed in 10.5w/15w and 26w Led chip in 3000K & 5600k CCT with >80 CRI and in 16, 18 & 20 degree beam angle. Downlight comes in with IP20 ingress protection	LED 1534-15	LED 1534-26
Model No								
LED 1534-10.5	The downlight is designed in 10.5w/15w and 26w Led chip in 3000K & 5600k CCT with >80 CRI and in 16, 18 & 20 degree beam angle. Downlight comes in with IP20 ingress protection							
LED 1534-15								
LED 1534-26								
	Maximo	<table><tr><th>Model No</th><th></th></tr><tr><td>LED 1535-50</td><td>Specially designed LED array mounted on die cast finned heat sink incorporating Synjet Active Cooling Technology. The downlight is designed for 50w Led chip.</td></tr></table>	Model No		LED 1535-50	Specially designed LED array mounted on die cast finned heat sink incorporating Synjet Active Cooling Technology. The downlight is designed for 50w Led chip.		
Model No								
LED 1535-50	Specially designed LED array mounted on die cast finned heat sink incorporating Synjet Active Cooling Technology. The downlight is designed for 50w Led chip.							
	Sandos	<table><tr><th>Model No</th><th></th></tr><tr><td>LED 1533-10.5</td><td rowspan="2">Sandos is surface mounted downlight. The downlight is designed for 10.5w and 15w Led chip in 3000K, 4000k & 5000k CCT with >80 CRI and in 22 degree beam angle.</td></tr><tr><td>LED 1533-15</td></tr></table>	Model No		LED 1533-10.5	Sandos is surface mounted downlight. The downlight is designed for 10.5w and 15w Led chip in 3000K, 4000k & 5000k CCT with >80 CRI and in 22 degree beam angle.	LED 1533-15	
Model No								
LED 1533-10.5	Sandos is surface mounted downlight. The downlight is designed for 10.5w and 15w Led chip in 3000K, 4000k & 5000k CCT with >80 CRI and in 22 degree beam angle.							
LED 1533-15								



	Troll	<p>Model No</p> <p>LED 1477-18 fixed Made of deep drawn aluminum housing in IP54 ingress protection The fixture comes in fixed and adjustable optics in 18w and 15w LED .</p> <p>LED 1477-15 ajustable</p>
	Corona	<p>Model No</p> <p>LED 1538-04/MR16</p> <p>LED 1538-06/MR16 Corona is an IP65 downlight which support MR16 and GU10 LED lamp. Available colour temperatures are 2700K, 3000K, 4000K CCT and it comes with 24/ 36 / 60 degrees beam angle in 4w , 6w and 10w .</p> <p>LED 1538-10/MR16</p> <p>LED 1538-04/GU10</p> <p>LED 1538-06/GU10</p>
	Volo	<p>Model No</p> <p>LED 1539-04/MR16</p> <p>LED 1539-06/MR16 Volo is an IP65 downlight which support MR16 and GU10 LED lamp. Available colour temperatures are 2700K, 3000K, 4000K CCT and it comes with 24/ 36 / 60 degrees beam angle in 4w , 6w and 10w .</p> <p>LED 1539-10/MR16</p> <p>LED 1539-04/GU10</p> <p>LED 1539-06/GU10</p>
	Capri	<p>Model No</p> <p>LED 1540-04/MR16</p> <p>LED 1540-06/MR16 Capri is an IP20 dropglass downlight which support MR16 and GU10 LED lamp. Available colour temperatures are 2700K, 3000K, 4000K CCT and it comes with 24/ 36 / 60 degrees beam angle in 4w , 6w and 10w .</p> <p>LED 1540-10/MR16</p> <p>LED 1540-04/GU10</p> <p>LED 1540-06/GU10</p>
	Vista	<p>Model No</p> <p>LED 1541-04/MR16</p> <p>LED 1541-06/MR16 Capri is an IP65 downlight which support MR16 and GU10 LED lamp. Available colour temperatures are 2700K, 3000K, 4000K CCT and it comes with 24/ 36 / 60 degrees beam angle in 4w , 6w and 10w .</p> <p>LED 1541-10/MR16</p> <p>LED 1541-04/GU10</p> <p>LED 1541-06/GU10</p>

	Mobile Nano	Model No	
		LED 1538-04/MR16	Mobile Nano is an IP20 downlight which support MR16 and GU10 LED lamp. Available colour temperatures are 2700K, 3000K, 4000K CCT and it comes with 24/ 36 / 60 degrees beam angle in 4w , 6w and 10w .
		LED 1538-06/MR16	
		LED 1538-10/MR16	
		LED 1538-04/GU10	
		LED 1538-06/GU10	


	Siena	Model No	
		LED1658-04/MR16	Siena has been designed with light source place deep inside to create an accent lighting but without glare. This fixture is suitable to illuminate shops, restaurants, hotels, and especially galleries, exhibitions and museums.
		LED 1658-06/MR16	
		LED 1658-10/MR16	Siena supports MR16 and GU10 LED lamp. Downlight comes in with IP20 ingress protection and is available in White, Black & Grey finish.
		LED 1658-04/GU10	
		LED 1658-06/GU10	

	Aqua	Model No	
		LED1656-04/MR16	Aqua has been specially designed downlight with finned die cast aluminum body with fixed head that supports MR16 and GU10 LED lamp.
		LED 1656-06/MR16	
		LED 1656-10/MR16	Downlight comes in with IP20 ingress protection and is available in White, Black & Grey finish.
		LED 1656-04/GU10	
		LED 1656-06/GU10	



	Alicia Nano	Model No	
		LED1657-04/MR16	Alicia Nano has been designed with invisible , adjustable lamp head in CRCA powder coated body that supports MR16 and GU10 LED lamp.
		LED 1657-06/MR16	
		LED 1657-10/MR16	Downlight comes in with IP20 ingress protection and is available in White, Black & Grey finish.
		LED 1657-04/GU10	
		LED 1657-06/GU10	

 	Retta	Model No
		LED 1650-110 -24/40
		LED 1650-115-24/40
		LED 1651-210-24/40
		LED 1651-215-24/40
		LED 1652-310-24/40
		LED 1652-315-24/40
		LED 1653-410-24/40
		LED 1653-415-24/40

Retta is adjustable head in single , double , triple and four head configuration in 10w and 15w .





 	Retta S	Model No
		LED 1666-104 -24/36/60
		LED 1666-106 -24/36/60
		LED 1666-110 -24/36/60
		LED 1667-204 -24/36/60
		LED 1667-206 -24/36/60
		LED 1667-210 -24/36/60
		LED 1668-304 -24/36/60
		LED 1668-306 -24/36/60
		LED 1668-310 -24/36/60
		LED 1669-404 -24/36/60
		LED 1669-406 -24/36/60
		LED 1669-410 -24/36/60

Retta S is adjustable head in single , double , triple and four head configuration in 4W , 6W and 10W .

 	TinyLux	Model No
		LED 1590-01/25
		LED 1591-01/25
		LED 1592-01/25
		LED 1593-01/25
		LED 1594-03/25
		LED 1595-01/25

TinyLux is specially designed LED luminaires for small window display lighting . Luminaires are made of aluminum with 1w LED embedded . These are non integral luminaires and seperate 6w constant current driver 350ma is used to feed 6 nos 1w luminaires .


	Rail	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1621-05/500</td><td rowspan="2">Aluminum extrusion body with builtin low voltage LED lights embedded illuminate the wardrobe when the door is opened. Available in 5w and 8w in 500mm and 1000mm length.</td></tr><tr><td>LED 1622-08/1000</td></tr></table>	Model No		LED 1621-05/500	Aluminum extrusion body with builtin low voltage LED lights embedded illuminate the wardrobe when the door is opened. Available in 5w and 8w in 500mm and 1000mm length.	LED 1622-08/1000
Model No							
LED 1621-05/500	Aluminum extrusion body with builtin low voltage LED lights embedded illuminate the wardrobe when the door is opened. Available in 5w and 8w in 500mm and 1000mm length.						
LED 1622-08/1000							
	Vivo	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1401-12</td><td rowspan="2">Made of pressure die cast aluminum with Opal PC lens. Available in two different sizes in 3w & 12w LED , its application is most suitable for Exterior Villa lighting , security lighting , Hallway, Hotels or simply as tall bollard .</td></tr><tr><td>LED 1402-03</td></tr></table>	Model No		LED 1401-12	Made of pressure die cast aluminum with Opal PC lens. Available in two different sizes in 3w & 12w LED , its application is most suitable for Exterior Villa lighting , security lighting , Hallway, Hotels or simply as tall bollard .	LED 1402-03
Model No							
LED 1401-12	Made of pressure die cast aluminum with Opal PC lens. Available in two different sizes in 3w & 12w LED , its application is most suitable for Exterior Villa lighting , security lighting , Hallway, Hotels or simply as tall bollard .						
LED 1402-03							
	Bella	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1404-03</td><td>Dynamic and versatile lighting system for general and accent lighting .Fixture creates dynamic effect if used wisely for interior or exterior spaces. Fixture is made in aluminum in 3 w Led .</td></tr></table>	Model No		LED 1404-03	Dynamic and versatile lighting system for general and accent lighting .Fixture creates dynamic effect if used wisely for interior or exterior spaces. Fixture is made in aluminum in 3 w Led .	
Model No							
LED 1404-03	Dynamic and versatile lighting system for general and accent lighting .Fixture creates dynamic effect if used wisely for interior or exterior spaces. Fixture is made in aluminum in 3 w Led .						
	Vela	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1405-06</td><td>Once anonymous – almost invisible and stunningly decorative. Fixture is made in pressure die cast aluminum with corrosion resistant powder coating in 3w+3w , up-down LED ..</td></tr></table>	Model No		LED 1405-06	Once anonymous – almost invisible and stunningly decorative. Fixture is made in pressure die cast aluminum with corrosion resistant powder coating in 3w+3w , up-down LED ..	
Model No							
LED 1405-06	Once anonymous – almost invisible and stunningly decorative. Fixture is made in pressure die cast aluminum with corrosion resistant powder coating in 3w+3w , up-down LED ..						
	Zen	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1403-05</td><td>Made of long-lasting die cast aluminum and perfect ingress protection ZEN is suitable for wall mounting. Zen is available in 5w energy efficient Led. ..</td></tr></table>	Model No		LED 1403-05	Made of long-lasting die cast aluminum and perfect ingress protection ZEN is suitable for wall mounting. Zen is available in 5w energy efficient Led. ..	
Model No							
LED 1403-05	Made of long-lasting die cast aluminum and perfect ingress protection ZEN is suitable for wall mounting. Zen is available in 5w energy efficient Led. ..						
	Stilo	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1407-03</td><td>Distinctive LED wall-mounted luminaire for the illumination of wellness spaces, pools, corridors or as supplementary lighting. Fixture is made of die cast aluminum in 3w Led.</td></tr></table>	Model No		LED 1407-03	Distinctive LED wall-mounted luminaire for the illumination of wellness spaces, pools, corridors or as supplementary lighting. Fixture is made of die cast aluminum in 3w Led.	
Model No							
LED 1407-03	Distinctive LED wall-mounted luminaire for the illumination of wellness spaces, pools, corridors or as supplementary lighting. Fixture is made of die cast aluminum in 3w Led.						
	Gimble	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED1408-03</td><td>Pressure die cast aluminum body with convex lens. Pure silicon gaskets to provide IP65 protection and stainless steel screws and hardware . Fixtures are thermally suitable to accept 3w smd Led.</td></tr></table>	Model No		LED1408-03	Pressure die cast aluminum body with convex lens. Pure silicon gaskets to provide IP65 protection and stainless steel screws and hardware . Fixtures are thermally suitable to accept 3w smd Led.	
Model No							
LED1408-03	Pressure die cast aluminum body with convex lens. Pure silicon gaskets to provide IP65 protection and stainless steel screws and hardware . Fixtures are thermally suitable to accept 3w smd Led.						


	Cubo	Model No	<p>LED 1410-07</p> <p>This luminaire supplies effective lighting wherever an effect of soft elegance is required. Pressure die cast housing with silicon gaskets and PC lens in 7w LED with IP54 make it ideal for indoor as well as outdoor application.</p>
	Cona	Model No	<p>LED1411-05</p> <p>Entirely produced in in die cast aluminium, offering single fixtures which can be utilised for hilighting Pillars , corners in residential or business premises , available in 5w LED .</p>
	Meso	Model No	<p>LED 1424-09</p> <p>Professional projectors for general and accent lighting. The constructive sturdiness of this fixtures produced in diecast aluminium is available in 9w LED .</p>
	Moon	Model No	<p>LED 1452-12</p> <p>A ceiling-mounting system for decorative lighting effects. Moon has been designed with innovative technologies and distributes the light flow evenly. Available in 12 w LED version .</p>
	Jinni	Model No	<p>LED 1520-06</p> <p>This compact LED wallpack combines efficiency and functionality with an attractive appearance. Made of die cast aluminum in IP65 ingress protection with PC lens available in 6w LED .</p>
	Orion	Model No	<p>LED 1457-19</p> <p>LED 1458-19</p> <p>LED 1459-19</p> <p>LED 1460-12</p> <p>LED 1461-12</p> <p>LED 1462-12</p> <p>Orion is surface mounted simplistic design which brings character to the wall it is pasted on. A well accepted generic design fixture made of pressure die cast aluminum, now available in energy efficient LED in two sizes 275mm and 220mm. Available wattages are 12w and 19w LED .</p>


	Brik	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1452-19</td><td rowspan="2">Brik, cleanline fixture which goes with the simple architecture, used for illuminating hallway, Villas, residential apartments, Hotels etc, can be used indoor as well as Outdoors. Made of pressure die cast aluminum with pure silicon gaskets and ss hardware the fixture is available in 12w Led.</td></tr><tr><td>LED 1453-19</td></tr></table>	Model No		LED 1452-19	Brik, cleanline fixture which goes with the simple architecture, used for illuminating hallway, Villas, residential apartments, Hotels etc, can be used indoor as well as Outdoors. Made of pressure die cast aluminum with pure silicon gaskets and ss hardware the fixture is available in 12w Led.	LED 1453-19				
Model No											
LED 1452-19	Brik, cleanline fixture which goes with the simple architecture, used for illuminating hallway, Villas, residential apartments, Hotels etc, can be used indoor as well as Outdoors. Made of pressure die cast aluminum with pure silicon gaskets and ss hardware the fixture is available in 12w Led.										
LED 1453-19											
	Ovale	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1463-07</td><td rowspan="6">Pressure die cast aluminum body with opal polycarbonate lens . Pure silicon gaskets to provide IP54 protection and stainless steel screws and hardware. Fixture is cromate converted before powder coating . Fixtures are thermally suitable to accept 7w master Led . Mounting thru specially designed eyelids at back plate . Application : Residential apartments , Hotels , Hospitals , Villas etc.</td></tr><tr><td>LED 1464-07</td></tr><tr><td>LED 1465-07</td></tr><tr><td>LED 1454-07</td></tr><tr><td>LED 1455-07</td></tr><tr><td>LED 1456-07</td></tr></table>	Model No		LED 1463-07	Pressure die cast aluminum body with opal polycarbonate lens . Pure silicon gaskets to provide IP54 protection and stainless steel screws and hardware. Fixture is cromate converted before powder coating . Fixtures are thermally suitable to accept 7w master Led . Mounting thru specially designed eyelids at back plate . Application : Residential apartments , Hotels , Hospitals , Villas etc.	LED 1464-07	LED 1465-07	LED 1454-07	LED 1455-07	LED 1456-07
Model No											
LED 1463-07	Pressure die cast aluminum body with opal polycarbonate lens . Pure silicon gaskets to provide IP54 protection and stainless steel screws and hardware. Fixture is cromate converted before powder coating . Fixtures are thermally suitable to accept 7w master Led . Mounting thru specially designed eyelids at back plate . Application : Residential apartments , Hotels , Hospitals , Villas etc.										
LED 1464-07											
LED 1465-07											
LED 1454-07											
LED 1455-07											
LED 1456-07											
	Iris-Q	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1431-03</td><td>Line of wall-mounted products, for indoor and outdoor use, designed to illuminate stairways, corridors, passageways and sidewalks. . Housing in pressure die cast with powder coat and stainless steel hardware makes it suitable for indoor and outdoor application .</td></tr></table>	Model No		LED 1431-03	Line of wall-mounted products, for indoor and outdoor use, designed to illuminate stairways, corridors, passageways and sidewalks. . Housing in pressure die cast with powder coat and stainless steel hardware makes it suitable for indoor and outdoor application .					
Model No											
LED 1431-03	Line of wall-mounted products, for indoor and outdoor use, designed to illuminate stairways, corridors, passageways and sidewalks. . Housing in pressure die cast with powder coat and stainless steel hardware makes it suitable for indoor and outdoor application .										
	Stepo	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1432-03</td><td rowspan="3">Lighting the space yet no glare to the pedestrianian , Stepo does its job it is designed for . Recess mounted goes flush with the wall . Made of die cast aluminum in IP65 ingress protection with powder coated externally, luminaire is available in three sizes and in 02, 03 and 05 watt Led</td></tr><tr><td>LED 1433-05</td></tr><tr><td>LED 1446-02</td></tr></table>	Model No		LED 1432-03	Lighting the space yet no glare to the pedestrianian , Stepo does its job it is designed for . Recess mounted goes flush with the wall . Made of die cast aluminum in IP65 ingress protection with powder coated externally, luminaire is available in three sizes and in 02, 03 and 05 watt Led	LED 1433-05	LED 1446-02			
Model No											
LED 1432-03	Lighting the space yet no glare to the pedestrianian , Stepo does its job it is designed for . Recess mounted goes flush with the wall . Made of die cast aluminum in IP65 ingress protection with powder coated externally, luminaire is available in three sizes and in 02, 03 and 05 watt Led										
LED 1433-05											
LED 1446-02											
	Neptune	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1445-1.2</td><td>Neptune is a recess mounted glare free light in round shape. Almost hidden the fixture offers subtle light which enhances the beauty of place as well as offers guidance. Fixture is made of die cast aluminum and is available in 1.2w LED</td></tr></table>	Model No		LED 1445-1.2	Neptune is a recess mounted glare free light in round shape. Almost hidden the fixture offers subtle light which enhances the beauty of place as well as offers guidance. Fixture is made of die cast aluminum and is available in 1.2w LED					
Model No											
LED 1445-1.2	Neptune is a recess mounted glare free light in round shape. Almost hidden the fixture offers subtle light which enhances the beauty of place as well as offers guidance. Fixture is made of die cast aluminum and is available in 1.2w LED										
	Iris-R	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1429-05</td><td>Line of wall-mounted products, for indoor and outdoor use, designed to illuminate stairways, corridors, passageways and sidewalks. Housing in pressure die cast with powder coat and stainless steel hardware makes it suitable for indoor and outdoor application .</td></tr></table>	Model No		LED 1429-05	Line of wall-mounted products, for indoor and outdoor use, designed to illuminate stairways, corridors, passageways and sidewalks. Housing in pressure die cast with powder coat and stainless steel hardware makes it suitable for indoor and outdoor application .					
Model No											
LED 1429-05	Line of wall-mounted products, for indoor and outdoor use, designed to illuminate stairways, corridors, passageways and sidewalks. Housing in pressure die cast with powder coat and stainless steel hardware makes it suitable for indoor and outdoor application .										


	Apollo	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1430-03</td><td>Apollo is a surface mounted semi cylindrical fixture made in aluminum. The fixture has been designed to go with the various architectural buildings and also to give pillared enhancement to flat surfaces. The fixture comes with smd type Led in 3w.</td></tr></table>	Model No		LED 1430-03	Apollo is a surface mounted semi cylindrical fixture made in aluminum. The fixture has been designed to go with the various architectural buildings and also to give pillared enhancement to flat surfaces. The fixture comes with smd type Led in 3w.						
Model No												
LED 1430-03	Apollo is a surface mounted semi cylindrical fixture made in aluminum. The fixture has been designed to go with the various architectural buildings and also to give pillared enhancement to flat surfaces. The fixture comes with smd type Led in 3w.											
	Neo	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1428-02</td><td rowspan="2">These surface & recessed fixtures with energy efficient LEDs create evocative light effects and are ideal for stairs, steps and ramps in general. Made of non corrosive aluminum body with powder coat using pure silicon gaskets and stainless steel hardware. Luminaire is available in 02w and 03 w Led</td></tr><tr><td>LED 1434-03</td></tr></table>	Model No		LED 1428-02	These surface & recessed fixtures with energy efficient LEDs create evocative light effects and are ideal for stairs, steps and ramps in general. Made of non corrosive aluminum body with powder coat using pure silicon gaskets and stainless steel hardware. Luminaire is available in 02w and 03 w Led	LED 1434-03					
Model No												
LED 1428-02	These surface & recessed fixtures with energy efficient LEDs create evocative light effects and are ideal for stairs, steps and ramps in general. Made of non corrosive aluminum body with powder coat using pure silicon gaskets and stainless steel hardware. Luminaire is available in 02w and 03 w Led											
LED 1434-03												
	Cendo	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1412-03</td><td rowspan="6">A wall-mounted range available with single or double beams. Cendo wall & ceiling is the newest addition to the wall washer line. The ceiling version is ideal for illuminating downwards in many types of areas including doorways, covered areas, entry ways and roofs. Cendo thrives on simplicity - clean lined in design and easy to install. Fixture is made of extruded aluminium cylinder, tempered safety glass, polyester powder coating, with a pluri-processed against corrosion & AISI 304 stainless steel hardware. Fixture is available in two sizes in 3w to 12w in single and double light emission .</td></tr><tr><td>LED 1413-03</td></tr><tr><td>LED 1414-06</td></tr><tr><td>LED 1418-06</td></tr><tr><td>LED 1419-06</td></tr><tr><td>LED 1420-12</td></tr></table>	Model No		LED 1412-03	A wall-mounted range available with single or double beams. Cendo wall & ceiling is the newest addition to the wall washer line. The ceiling version is ideal for illuminating downwards in many types of areas including doorways, covered areas, entry ways and roofs. Cendo thrives on simplicity - clean lined in design and easy to install. Fixture is made of extruded aluminium cylinder, tempered safety glass, polyester powder coating, with a pluri-processed against corrosion & AISI 304 stainless steel hardware. Fixture is available in two sizes in 3w to 12w in single and double light emission .	LED 1413-03	LED 1414-06	LED 1418-06	LED 1419-06	LED 1420-12	
Model No												
LED 1412-03	A wall-mounted range available with single or double beams. Cendo wall & ceiling is the newest addition to the wall washer line. The ceiling version is ideal for illuminating downwards in many types of areas including doorways, covered areas, entry ways and roofs. Cendo thrives on simplicity - clean lined in design and easy to install. Fixture is made of extruded aluminium cylinder, tempered safety glass, polyester powder coating, with a pluri-processed against corrosion & AISI 304 stainless steel hardware. Fixture is available in two sizes in 3w to 12w in single and double light emission .											
LED 1413-03												
LED 1414-06												
LED 1418-06												
LED 1419-06												
LED 1420-12												
	Box	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1415-03</td><td rowspan="2">Box offers lighting system for general and accent lighting of exhibition spaces, museums, retail outlets and modern residential buildings.</td></tr><tr><td>LED 1416-03</td></tr><tr><td>LED 1417-06</td><td rowspan="4">Simple construction hides the complex technical features offering the best heat dissipation to the Led light source, made of studier die cast aluminum and tempered lens . Fixture available in two sizes.</td></tr><tr><td>LED 1421-06</td></tr><tr><td>LED 1422-06</td></tr><tr><td>LED 1423-12</td></tr></table>	Model No		LED 1415-03	Box offers lighting system for general and accent lighting of exhibition spaces, museums, retail outlets and modern residential buildings.	LED 1416-03	LED 1417-06	Simple construction hides the complex technical features offering the best heat dissipation to the Led light source, made of studier die cast aluminum and tempered lens . Fixture available in two sizes.	LED 1421-06	LED 1422-06	LED 1423-12
Model No												
LED 1415-03	Box offers lighting system for general and accent lighting of exhibition spaces, museums, retail outlets and modern residential buildings.											
LED 1416-03												
LED 1417-06	Simple construction hides the complex technical features offering the best heat dissipation to the Led light source, made of studier die cast aluminum and tempered lens . Fixture available in two sizes.											
LED 1421-06												
LED 1422-06												
LED 1423-12												
	Polo	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1304-10</td><td>Harmonious by day, romantic by night. Polo is the antithesis of the "decorative" Bollard which emits the balanced and non polluting light . Fixture is made of die cast aluminum housing with non corrosive powder coating in IP66 protection with 10w smd Led .</td></tr></table>	Model No		LED 1304-10	Harmonious by day, romantic by night. Polo is the antithesis of the "decorative" Bollard which emits the balanced and non polluting light . Fixture is made of die cast aluminum housing with non corrosive powder coating in IP66 protection with 10w smd Led .						
Model No												
LED 1304-10	Harmonious by day, romantic by night. Polo is the antithesis of the "decorative" Bollard which emits the balanced and non polluting light . Fixture is made of die cast aluminum housing with non corrosive powder coating in IP66 protection with 10w smd Led .											


	Neero	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1479- R-CX</td><td>Die-cast aluminium head unit with clear polycarbonate outer tube.</td></tr><tr><td>LED 1479-R-CE</td><td>Shaft made of aluminum tube, externally powder coated, with Integral control gear. Mounting height 800/1000mm. Access to the lamp and control gear by removing the head. Bollards in round head and</td></tr><tr><td>LED 1480-F-CX</td><td>flat head are available in two special Convex and Concave Optics to</td></tr><tr><td>LED 1480-F-CE</td><td>create dynamic surroundings in energy efficient 7w Led.</td></tr></table>	Model No		LED 1479- R-CX	Die-cast aluminium head unit with clear polycarbonate outer tube.	LED 1479-R-CE	Shaft made of aluminum tube, externally powder coated, with Integral control gear. Mounting height 800/1000mm. Access to the lamp and control gear by removing the head. Bollards in round head and	LED 1480-F-CX	flat head are available in two special Convex and Concave Optics to	LED 1480-F-CE	create dynamic surroundings in energy efficient 7w Led.
Model No												
LED 1479- R-CX	Die-cast aluminium head unit with clear polycarbonate outer tube.											
LED 1479-R-CE	Shaft made of aluminum tube, externally powder coated, with Integral control gear. Mounting height 800/1000mm. Access to the lamp and control gear by removing the head. Bollards in round head and											
LED 1480-F-CX	flat head are available in two special Convex and Concave Optics to											
LED 1480-F-CE	create dynamic surroundings in energy efficient 7w Led.											
	Luxor	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1427-08</td><td>Luxor LED is made of extrusion aluminium square pipe of high thermal conductivity. Excellent powder coating ensures high protection and excellent long life and is available in 650mm height with 8w smd Led .</td></tr></table>	Model No		LED 1427-08	Luxor LED is made of extrusion aluminium square pipe of high thermal conductivity. Excellent powder coating ensures high protection and excellent long life and is available in 650mm height with 8w smd Led .						
Model No												
LED 1427-08	Luxor LED is made of extrusion aluminium square pipe of high thermal conductivity. Excellent powder coating ensures high protection and excellent long life and is available in 650mm height with 8w smd Led .											
	Rondo, Vento	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1425-6</td><td>Arch shape beautifully designed luminaires, can be used both for indoor and outdoor application. . Both the</td></tr><tr><td>LED 1426-9</td><td>fixtures are made of aluminum die cast and available in 6w and 9w .</td></tr></table>	Model No		LED 1425-6	Arch shape beautifully designed luminaires, can be used both for indoor and outdoor application. . Both the	LED 1426-9	fixtures are made of aluminum die cast and available in 6w and 9w .				
Model No												
LED 1425-6	Arch shape beautifully designed luminaires, can be used both for indoor and outdoor application. . Both the											
LED 1426-9	fixtures are made of aluminum die cast and available in 6w and 9w .											
	Nova	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1425-6</td><td>Simplistic yet innovative enough for interior as well as exterior applications. Made in aluminum with polycarbonate lens, Nova supports</td></tr><tr><td>LED 1426-9</td><td>highly efficient 7w master Leds. Fixture is available in wall mount and</td></tr><tr><td>LED 1426-9</td><td>base mount models</td></tr></table>	Model No		LED 1425-6	Simplistic yet innovative enough for interior as well as exterior applications. Made in aluminum with polycarbonate lens, Nova supports	LED 1426-9	highly efficient 7w master Leds. Fixture is available in wall mount and	LED 1426-9	base mount models		
Model No												
LED 1425-6	Simplistic yet innovative enough for interior as well as exterior applications. Made in aluminum with polycarbonate lens, Nova supports											
LED 1426-9	highly efficient 7w master Leds. Fixture is available in wall mount and											
LED 1426-9	base mount models											
	Quanto	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1450-07</td><td>Produced in sturdy, long-lasting aluminum die cast , Quanto is equipped with high-performance, optics to optimize lamp performance and lower operating costs. Fixture is with 7w LED .</td></tr></table>	Model No		LED 1450-07	Produced in sturdy, long-lasting aluminum die cast , Quanto is equipped with high-performance, optics to optimize lamp performance and lower operating costs. Fixture is with 7w LED .						
Model No												
LED 1450-07	Produced in sturdy, long-lasting aluminum die cast , Quanto is equipped with high-performance, optics to optimize lamp performance and lower operating costs. Fixture is with 7w LED .											
	Punto	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1451-07</td><td>The clean and linear design of the Punto has been developed with an eye to smoothly lighting surrounding surfaces. Fixture produced in die cast aluminium, with PC lens , Fixture is with 7w LED .</td></tr></table>	Model No		LED 1451-07	The clean and linear design of the Punto has been developed with an eye to smoothly lighting surrounding surfaces. Fixture produced in die cast aluminium, with PC lens , Fixture is with 7w LED .						
Model No												
LED 1451-07	The clean and linear design of the Punto has been developed with an eye to smoothly lighting surrounding surfaces. Fixture produced in die cast aluminium, with PC lens , Fixture is with 7w LED .											
	IDUS	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED1665-20</td><td>IDUS is made in corrosion free extrusion aluminium and vandal resistant PC or tempered glass , giving it superior durability.</td></tr><tr><td>LED 1665-40</td><td>It is available in height of 3.8m in powder coated black as standard in 20w and 40w LED .</td></tr></table>	Model No		LED1665-20	IDUS is made in corrosion free extrusion aluminium and vandal resistant PC or tempered glass , giving it superior durability.	LED 1665-40	It is available in height of 3.8m in powder coated black as standard in 20w and 40w LED .				
Model No												
LED1665-20	IDUS is made in corrosion free extrusion aluminium and vandal resistant PC or tempered glass , giving it superior durability.											
LED 1665-40	It is available in height of 3.8m in powder coated black as standard in 20w and 40w LED .											


	Inox	Model No
		<p>LED 1482-01A Enhancing space while keeping low profile, Inox has been designed to create ambiance . Suitable for Wall or Floor mounting, Inox is completely made in Stainless Steel with IP67 ingress protection .</p> <p>LED 1482-01B It is available 15/30/45/60 degree beam and in 1w and 3w options.</p> <p>LED 1482-01C</p> <p>LED 1482-01D</p> <p>LED 1483-03A</p> <p>LED 1483-03B</p> <p>LED 1483-03C</p> <p>LED 1483-03D</p>


	Atom	Model No
		<p>LED 1437-01 Complete Atom line made of non corrosive aluminum body with IP67 , SS cover plate in 1 watt and 3 watt Led</p> <p>LED 1438-03</p> <p>LED 1439-01</p> <p>LED 1440-03</p>


	Tile	Model No
		<p>LED 1485-06A Recessed wall and floor mounted luminaires draw the attention of architectural features.</p> <p>LED 1485-06B • Light proof housing made of die cast aluminum</p> <p>LED 1485-06C • Tempered safety glass, clear or matt</p> <p>• Protection class IP 67.</p> <p>LED 1486-14.5A • SS Cover</p> <p>LED 1486-14.5B • Beam Angles - 15°, 30°, 45° & 45°</p> <p>LED 1486-14.5C</p>

	Disk	Model No
		<p>LED 1208-35 /15 Disk fixtures, completely made of die cast body with SS304 cover plate, are suitable to be installed in environments with aggressive weather conditions. Suitable for vehicular and pedestrian traffic as well. Available in IP67 ingress protection with energy efficient 3w, 18w and 35w LED. Available optics in beam angles of 15/30/45 & 60 degrees</p> <p>LED 1208-35 /30</p> <p>LED 1208-35 /45</p> <p>LED 1208-35 /60</p>


Disk cont..		Model No
		LED 1209-18/15
		LED 1209-18/30
		LED 1209-18/45
		LED 1209-18/60
		LED 1210-03/15
		LED 1210-03/30
		LED 1210-03/45
		LED 1210-03/60


Linea		Model No
		LED 1203-20
		LED 1203-10
		LED 1203-14
		Linea is a complete system, which, via technologically evolved leds, is able to adapt itself to the most diverse architecture, building exteriors, facades, etc. Made of extruded aluminum with tempered glass in IP67 ingress protection in 10w, 14w and 20w in 1000mm length .


H ₂ O-Beam		Model No
		LED 1575-9 (SY/ASY)
		LED 1576-18 (SY/ASY)
		LED 1577-18
		LED 1578-18
		LED 1579-12
		H2O beam is collection of luminaires for illuminating Fountains , Swimming Pools and water bodies. All luminaires are made of stainless steel with IP68 Ingress Protection Class. LEDs available in cool white /warm white colour


H ₂ O flood		Model No
		LED 1560-7.5/15
		LED 1560-7.5/30
		LED 1560-7.5/45
		LED 1560-7.5/60
		LED 1561-15/15
		LED 1561-15/30
		LED 1561-15/45
		LED 1561-15/60
		With H2O range our designers have created luminaires that cannot fail to impress with their straightforward, slim lines and highly expressive, refined stainless steel grade 316 materials. H2O discreetly fits into the water body without ever upstaging the architect's or designer's vision. The emphasis is on the light, not on the luminaire. Due to LED technology, the light effect created by these luminaires is precise and highly effective which could not be achieved so far with gas discharge lamps. Luminaires come with IP68 ingress protection and suitable for fountain lighting / water-bodies lighting, River, stream lighting , Under bridge lighting etc. Various optics in 15 deg/30 deg/45 deg and 60 deg available


	H₂O flood	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1562-30/15</td><td rowspan="8"></td></tr><tr><td>LED 1562-30/30</td></tr><tr><td>LED 1562-30/45</td></tr><tr><td>LED 1562-30/60</td></tr><tr><td>LED 1563-45/15</td></tr><tr><td>LED 1563-45/30</td></tr><tr><td>LED 1563-45/45</td></tr><tr><td>LED 1563-45/60</td></tr></table>	Model No		LED 1562-30/15		LED 1562-30/30	LED 1562-30/45	LED 1562-30/60	LED 1563-45/15	LED 1563-45/30	LED 1563-45/45	LED 1563-45/60
Model No													
LED 1562-30/15													
LED 1562-30/30													
LED 1562-30/45													
LED 1562-30/60													
LED 1563-45/15													
LED 1563-45/30													
LED 1563-45/45													
LED 1563-45/60													
	Powerlux	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1633-80</td><td rowspan="6">PowerLux Highbay is a clear example of stylistic idiom and high functionality. Fixture optics is designed for maximum intensity and no light scattering. Fixture is made of die cast aluminum with special fins on reflector for better heat dissipation. PowerLux is available in two sizes, smaller version is upto 120w and bigger version is upto 200w.</td></tr><tr><td>LED 1633-100</td></tr><tr><td>LED 1633-120</td></tr><tr><td>LED 1634-150</td></tr><tr><td>LED 1634-180</td></tr><tr><td>LED 1634-200</td></tr></table>	Model No		LED 1633-80	PowerLux Highbay is a clear example of stylistic idiom and high functionality. Fixture optics is designed for maximum intensity and no light scattering. Fixture is made of die cast aluminum with special fins on reflector for better heat dissipation. PowerLux is available in two sizes, smaller version is upto 120w and bigger version is upto 200w.	LED 1633-100	LED 1633-120	LED 1634-150	LED 1634-180	LED 1634-200		
Model No													
LED 1633-80	PowerLux Highbay is a clear example of stylistic idiom and high functionality. Fixture optics is designed for maximum intensity and no light scattering. Fixture is made of die cast aluminum with special fins on reflector for better heat dissipation. PowerLux is available in two sizes, smaller version is upto 120w and bigger version is upto 200w.												
LED 1633-100													
LED 1633-120													
LED 1634-150													
LED 1634-180													
LED 1634-200													
	Titan	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1635-35</td><td rowspan="3">Excellent design of Titan allows professionals to design lighting installations with the utmost flexibility and lowest costs. Ceiling mount or hanging, both versions available. Fixture is made of aluminum extrusion with PC diffuser achieving IP66 protection class in 35w, 45w and 70w LED .</td></tr><tr><td>LED 1636-45</td></tr><tr><td>LED 1637-70</td></tr></table>	Model No		LED 1635-35	Excellent design of Titan allows professionals to design lighting installations with the utmost flexibility and lowest costs. Ceiling mount or hanging, both versions available. Fixture is made of aluminum extrusion with PC diffuser achieving IP66 protection class in 35w, 45w and 70w LED .	LED 1636-45	LED 1637-70					
Model No													
LED 1635-35	Excellent design of Titan allows professionals to design lighting installations with the utmost flexibility and lowest costs. Ceiling mount or hanging, both versions available. Fixture is made of aluminum extrusion with PC diffuser achieving IP66 protection class in 35w, 45w and 70w LED .												
LED 1636-45													
LED 1637-70													
	Indure	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1110-90</td><td rowspan="2">Indure is designed to take advantage of direct lighting for large architecturally significant buildings. Component compartment made of extruded aluminium with die-cast aluminium end caps. Fixture is available in 90w and 120w Led.</td></tr><tr><td>LED 1110-120</td></tr></table>	Model No		LED 1110-90	Indure is designed to take advantage of direct lighting for large architecturally significant buildings. Component compartment made of extruded aluminium with die-cast aluminium end caps. Fixture is available in 90w and 120w Led.	LED 1110-120						
Model No													
LED 1110-90	Indure is designed to take advantage of direct lighting for large architecturally significant buildings. Component compartment made of extruded aluminium with die-cast aluminium end caps. Fixture is available in 90w and 120w Led.												
LED 1110-120													
	Sundown	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1112-90</td><td rowspan="3">A particularly interesting technology has been employed in the sundown pendant model, which features micro-prismatic anti-glare optics. Fixture is made of die cast aluminum with special fins on reflector for better heat dissipation. Sundown is available in 498mm dia sizes, in 90w/115w and 140w Led</td></tr><tr><td>LED 1112-115</td></tr><tr><td>LED 1112-140</td></tr></table>	Model No		LED 1112-90	A particularly interesting technology has been employed in the sundown pendant model, which features micro-prismatic anti-glare optics. Fixture is made of die cast aluminum with special fins on reflector for better heat dissipation. Sundown is available in 498mm dia sizes, in 90w/115w and 140w Led	LED 1112-115	LED 1112-140					
Model No													
LED 1112-90	A particularly interesting technology has been employed in the sundown pendant model, which features micro-prismatic anti-glare optics. Fixture is made of die cast aluminum with special fins on reflector for better heat dissipation. Sundown is available in 498mm dia sizes, in 90w/115w and 140w Led												
LED 1112-115													
LED 1112-140													


	Pulsar	Model No	
		LED 1490-70	<p>The first of its kind, the Sololuce Pulsar Series LED High Bay luminaires were designed specifically to replace conventional high bay lighting fixtures in locations like Factories, Exhibition Halls, Warehouses, Hypermarkets, Airport Hangers, Ports etc. Luminaires are made in pressure die cast aluminum, silicon gaskets, SS hardware and powdercoated externally.</p> <p>Fixtures come with IP66 ingress protection. Available from 70w till 200w .</p>
		LED 1491-100	
		LED 1492-130	
		LED 1493-160	
		LED 1494-200	

	Optagon	Model No	
		LED 1478-25	An exclusive design where high performance meets top-quality finishes. The round shape, offers more surface area to allow better heat dissipation in this compact size .
		LED 1478-40	
		LED 1478-60	Die cast aluminum fixture is available in 25w,40w & 60w Led in IP66 protection class .


	Notte	Model No	
		LED 1475-30	Notte stands for modern luminaire design for shopping centres and exhibition spaces . Housing is made of heat dissipating cooling fins made of aluminum extrusion profile , aluminum reflector with frosted drop glass with weather resistant powder coat after cromate concersion process .
		LED 1475-50	


	Tiara	Model No	
		LED 1499-12	Tiara thus seamlessly integrates into modern architectural surroundings and excels as a modern intervention in heritage buildings. Housing is made of heat dissipating cooling fins made of die cast aluminum , aluminum reflector with front glass with weather resistant powder coat.


	Duetto	Model No	
		LED 1630-14	LED in the heart of fixture with round opal polycarbonate tube with endcaps offers energy efficient solutions for
		LED 1631-24	lighting Underground Tunnels, Railway stations, Bus stops, parking areas, pathways in both wall or ceiling mount
		LED 1632-35	applications available in 14w , 24w and 35w LED


	Policar	Model No	
		LED 1470-18	A polycarbonate exterior and an original and technological design makes these LED fittings stand out. IP66 certifies the elevated resistance to dust and water penetration Available in two lengths 600 and 1200 mm, in two wattages of 18 and 36w .
		LED 1471-36	


	Policar Ecoled	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1616-10</td><td rowspan="3">Sleek polycarbonate exterior body with MCPCB with Leds mounted on it with requisite thermal heat dissipation .. IP66 certifies the elevated resistance to dust and water penetration Available in three lengths & wattages of 10w, 20w and 28w .</td></tr><tr><td>LED 1617-20</td></tr><tr><td>LED 1618-28</td></tr></table>	Model No		LED 1616-10	Sleek polycarbonate exterior body with MCPCB with Leds mounted on it with requisite thermal heat dissipation .. IP66 certifies the elevated resistance to dust and water penetration Available in three lengths & wattages of 10w, 20w and 28w .	LED 1617-20	LED 1618-28	
Model No									
LED 1616-10	Sleek polycarbonate exterior body with MCPCB with Leds mounted on it with requisite thermal heat dissipation .. IP66 certifies the elevated resistance to dust and water penetration Available in three lengths & wattages of 10w, 20w and 28w .								
LED 1617-20									
LED 1618-28									
	Luna	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1472-15</td><td rowspan="2">Simplistic Luna hides the most intricate electronic inside. Intelligent Heat dissipation designed without destroying the beauty of luminaire. Surface mounted Polycarbonate fixture suitable for car parks, Halls, Foyers and Hypermarkets. Available in two sizes of 300mm and 350mm with smd mounted Led of 15w and 20w. Clear/opal polycarbonate cover option available.</td></tr><tr><td>LED 1473-20</td></tr></table>	Model No		LED 1472-15	Simplistic Luna hides the most intricate electronic inside. Intelligent Heat dissipation designed without destroying the beauty of luminaire. Surface mounted Polycarbonate fixture suitable for car parks, Halls, Foyers and Hypermarkets. Available in two sizes of 300mm and 350mm with smd mounted Led of 15w and 20w. Clear/opal polycarbonate cover option available.	LED 1473-20		
Model No									
LED 1472-15	Simplistic Luna hides the most intricate electronic inside. Intelligent Heat dissipation designed without destroying the beauty of luminaire. Surface mounted Polycarbonate fixture suitable for car parks, Halls, Foyers and Hypermarkets. Available in two sizes of 300mm and 350mm with smd mounted Led of 15w and 20w. Clear/opal polycarbonate cover option available.								
LED 1473-20									
	Canlux	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1495-80</td><td rowspan="4">Canlux is efficient , low glare, recessed / surface-mounted specially designed luminaire for lighting of filling stations and other canopies. Luminaire is available in 80w and 100w led with 130 degree optics . Designed for surface as well as recess mounting on a false ceiling.</td></tr><tr><td>LED 1495-100</td></tr><tr><td>LED 1496-80</td></tr><tr><td>LED 1496-100</td></tr></table>	Model No		LED 1495-80	Canlux is efficient , low glare, recessed / surface-mounted specially designed luminaire for lighting of filling stations and other canopies. Luminaire is available in 80w and 100w led with 130 degree optics . Designed for surface as well as recess mounting on a false ceiling.	LED 1495-100	LED 1496-80	LED 1496-100
Model No									
LED 1495-80	Canlux is efficient , low glare, recessed / surface-mounted specially designed luminaire for lighting of filling stations and other canopies. Luminaire is available in 80w and 100w led with 130 degree optics . Designed for surface as well as recess mounting on a false ceiling.								
LED 1495-100									
LED 1496-80									
LED 1496-100									
	Xenon, Proton	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1466-15</td><td rowspan="2">Xenon and Proton are Infrared Motion Sensor based LED ceiling luminaire which can identify day and night automatically, adopting PIR sensor and integrated circuit. When a human body enters its detecting zone, the PIR sensor's light goes on, once leaving, the light will goes off according to its setting time.</td></tr><tr><td>LED 1481-90</td></tr></table>	Model No		LED 1466-15	Xenon and Proton are Infrared Motion Sensor based LED ceiling luminaire which can identify day and night automatically, adopting PIR sensor and integrated circuit. When a human body enters its detecting zone, the PIR sensor's light goes on, once leaving, the light will goes off according to its setting time.	LED 1481-90		
Model No									
LED 1466-15	Xenon and Proton are Infrared Motion Sensor based LED ceiling luminaire which can identify day and night automatically, adopting PIR sensor and integrated circuit. When a human body enters its detecting zone, the PIR sensor's light goes on, once leaving, the light will goes off according to its setting time.								
LED 1481-90									
	Electron	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1467-15</td><td rowspan="3">Electron is a Infrared Motion Sensor based LED Floodlight which can identify day and night automatically, adopting PIR sensor and integrated circuit. Available in 15w , 28w and 48w LED .</td></tr><tr><td>LED 1468-28</td></tr><tr><td>LED 1469-48</td></tr></table>	Model No		LED 1467-15	Electron is a Infrared Motion Sensor based LED Floodlight which can identify day and night automatically, adopting PIR sensor and integrated circuit. Available in 15w , 28w and 48w LED .	LED 1468-28	LED 1469-48	
Model No									
LED 1467-15	Electron is a Infrared Motion Sensor based LED Floodlight which can identify day and night automatically, adopting PIR sensor and integrated circuit. Available in 15w , 28w and 48w LED .								
LED 1468-28									
LED 1469-48									
	Line	<table><tr><th colspan="2">Model No</th></tr><tr><td>LED 1435-3.6</td><td rowspan="2">Line is made of corrosion resistant extruded aluminium body, tempered safety glass, mechanical and thermal shock resistant, corrosion resistant die-cast aluminium endcaps .Available in 3.6w and 6w in 300mm and 500mm length .</td></tr><tr><td>LED 1436-6</td></tr></table>	Model No		LED 1435-3.6	Line is made of corrosion resistant extruded aluminium body, tempered safety glass, mechanical and thermal shock resistant, corrosion resistant die-cast aluminium endcaps .Available in 3.6w and 6w in 300mm and 500mm length .	LED 1436-6		
Model No									
LED 1435-3.6	Line is made of corrosion resistant extruded aluminium body, tempered safety glass, mechanical and thermal shock resistant, corrosion resistant die-cast aluminium endcaps .Available in 3.6w and 6w in 300mm and 500mm length .								
LED 1436-6									




	Bar	Model No	
		LED 1521-4.5	Creating ambience or just as functional light Bar does both jobs efficiently. Made of aluminium extrusion body with silicon cover, Bar has IP54 protection. It is available in 4.5w, 7.5w and 15w, in 3000, 6000 or Amber+White mix colour
		LED 1522-7.5	
		LED 1523-15	


	Mini-Bar	Model No	
		LED 1525-1.44	Made of aluminium extrusion body with silicon cover, Mini-Bar has IP54 protection. It is available in 1.44w, 2.16 and 2.88 w, in 3000, 6000 or Amber+White mix colour.
		LED 1526-2.16	
		LED 1527-2.88	


	CabLux	Model No	
		LED 1550-4.8	With transparent endcover connectors Cablux is a continuous-row Lighting system. The top cover is polycarbonate sleeve which offers the LED an IP54 protection. CabLux is available in 4.8w and 9.6w, in 3000, 6000 or Red, Blue, Green, Yellow and Amber colour. Standard lengths available are 500mm and 1000mm.
		LED 1551-9.8	

	CabLux II	Model No	
		LED 1552-04	Cabinet lighting system is an individual luminaire or continus row system offers solutions for a wide range of applications – from Cove Lighting, undercabinet lights, cupboard lighting, kitchen shelf,showcase lighting and ambience lighting. Made of aluminium extrusion body with opaque cover, CabLux II has IP54 protection. It is available in 4W, 7W, 11W and 14 W, in 3000, & 6000 colour.
		LED 1553-07	
		LED 1554-11	
		LED 1555-14	

	CabLux III	Model No	
		LED 1587-5	Specially designed aluminum extrusion Cablux solves all the lighting requirements of Cabinet Lighting, Wardrobe Lighting, Accent Lighting , Bar Lighting and Mood Lighting etc .
		LED 1587-10	
		LED 1588-5	Cablux is available in two versions with IR switch and Touch Switch in 5w and 10w LED .
		LED 1588-10	






	Colourbright	Model No
		<p>LED 1581-24 Super bright LED strip lights with 3528/5050 SMD LEDs</p>
		<p>LED 1581-48 Our Colorbright series offers super bright LED strips in multiple colors like red, green, blue, warm white, and bright white.</p>
		<p>LED 1581-36 Residential grade LED strip lighting is perfect for accent lighting, under cabinet lighting, bar lighting, task lighting, TV backlighting, and pretty much anything you can think of. Our LED strip lights are flexible enough to bend around corners. We use the highest quality 3528 or 5050 LEDs.</p> <p>LED 1581-72 We have strips in IP20 for indoor application and IP66 for outdoor application .</p> <p>LED 1582-24</p> <p>LED 1582-48</p> <p>LED 1582-36</p> <p>LED 1582-72</p> <p>LED 1583-96</p> <p>LED 1583-96</p>


	Reflex	Model No
		<p>LED 1625-12 The reflex versions of the indoor series are the transposition of the concept of "soft light"(direct plus indirect) meant as a new frontier of lighting quality, that has been very successful for creating ambience in indoor. Quality in light means total absence of glare, perfect diffusion and great visual comfort.</p> <p>LED 1626-12</p> <p>LED 1627-08</p> <p>LED 1628-12 Made of Polycarbonate top shade with inbuilt LED and aluminum stand with touch dimming option as standard.</p> <p>LED 1629-08</p>


	Sierra	Model No
		<p>LED 1641-15 Light emanating out of specially engineered omni directional optics. This 15w LED fixture creates ambience for indoor as well as outdoor spaces. Fixture has base made in pressure die cast aluminum with externally powder coated in IP54 protection class.</p>

Fluorescent Lighting


Sololuce Fluorescent Lighting


	Exe	<table><tr><th colspan="2">Model No</th></tr><tr><td>FTL5107-228 PMMA</td><td rowspan="2">Aluminum profile frame with aluminum reflector & externally Silver grey/white thermopainted. Aluminum reflector with PMMA diffuser or I louvre/ 10% uplight & 90% downlight It is available 2X28w T5 lamp .</td></tr><tr><td>FTL 5107 -228 -I LOUVRE</td></tr></table>	Model No		FTL5107-228 PMMA	Aluminum profile frame with aluminum reflector & externally Silver grey/white thermopainted. Aluminum reflector with PMMA diffuser or I louvre/ 10% uplight & 90% downlight It is available 2X28w T5 lamp .	FTL 5107 -228 -I LOUVRE		
Model No									
FTL5107-228 PMMA	Aluminum profile frame with aluminum reflector & externally Silver grey/white thermopainted. Aluminum reflector with PMMA diffuser or I louvre/ 10% uplight & 90% downlight It is available 2X28w T5 lamp .								
FTL 5107 -228 -I LOUVRE									
	Avent	<table><tr><th colspan="2">Model No</th></tr><tr><td>FTL5103-228</td><td rowspan="2">Luminaire is made of aluminum extrusion profile with opal PMMA diffuser Silver grey thermopainted .It opens up 90% light in upward direction and 10% light downwards . Available in 2x28w T5 and 2x35 T5 lamp options .</td></tr><tr><td>FTL5103-235</td></tr></table>	Model No		FTL5103-228	Luminaire is made of aluminum extrusion profile with opal PMMA diffuser Silver grey thermopainted .It opens up 90% light in upward direction and 10% light downwards . Available in 2x28w T5 and 2x35 T5 lamp options .	FTL5103-235		
Model No									
FTL5103-228	Luminaire is made of aluminum extrusion profile with opal PMMA diffuser Silver grey thermopainted .It opens up 90% light in upward direction and 10% light downwards . Available in 2x28w T5 and 2x35 T5 lamp options .								
FTL5103-235									
	Magnum	<table><tr><th colspan="2">Model No</th></tr><tr><td>FTL5104-228 PMMA</td><td rowspan="4">Minimalist design and lighting comfort for office settings in just 50mm thickness. Magnum is the result of toplevel aesthetic and lighting design research which joins innovative and functional design with state-of-the-art lighting technology.Available in 2x28w T5 and 2x35 T5 lamp options .</td></tr><tr><td>FTL5104-235 PMMA</td></tr><tr><td>FTL5104-228 I LOUVER</td></tr><tr><td>FTL5104-235 I LOUVER</td></tr></table>	Model No		FTL5104-228 PMMA	Minimalist design and lighting comfort for office settings in just 50mm thickness. Magnum is the result of toplevel aesthetic and lighting design research which joins innovative and functional design with state-of-the-art lighting technology.Available in 2x28w T5 and 2x35 T5 lamp options .	FTL5104-235 PMMA	FTL5104-228 I LOUVER	FTL5104-235 I LOUVER
Model No									
FTL5104-228 PMMA	Minimalist design and lighting comfort for office settings in just 50mm thickness. Magnum is the result of toplevel aesthetic and lighting design research which joins innovative and functional design with state-of-the-art lighting technology.Available in 2x28w T5 and 2x35 T5 lamp options .								
FTL5104-235 PMMA									
FTL5104-228 I LOUVER									
FTL5104-235 I LOUVER									
	Extend	<table><tr><th colspan="2">Model No</th></tr><tr><td>FTL5105-328</td><td rowspan="2">Aluminum profile frame with extruded central pipe and semi-transparent prismatic PMMA diffuser. Silver grey thermopainted Aluminum reflectors with 60% uplight and 40% downlight.. Available in 3x28w T5 and 3x35 T5 lamp options .</td></tr><tr><td>FTL5105-335</td></tr></table>	Model No		FTL5105-328	Aluminum profile frame with extruded central pipe and semi-transparent prismatic PMMA diffuser. Silver grey thermopainted Aluminum reflectors with 60% uplight and 40% downlight.. Available in 3x28w T5 and 3x35 T5 lamp options .	FTL5105-335		
Model No									
FTL5105-328	Aluminum profile frame with extruded central pipe and semi-transparent prismatic PMMA diffuser. Silver grey thermopainted Aluminum reflectors with 60% uplight and 40% downlight.. Available in 3x28w T5 and 3x35 T5 lamp options .								
FTL5105-335									
	Optimus	<table><tr><th colspan="2">Model No</th></tr><tr><td>FTL5106-128</td><td rowspan="4">Aluminum profile frame with aluminum reflector, ABS end caps and Silver grey/white thermopainted Aluminum reflector with PMMA diffuser or I louvre/ 100% downlight.Available in 1x28w 2x28wT5 and 1x35 w and 2x35 T5 lamp options .</td></tr><tr><td>FTL5106-228</td></tr><tr><td>FTL5106-135</td></tr><tr><td>FTL5106-235</td></tr></table>	Model No		FTL5106-128	Aluminum profile frame with aluminum reflector, ABS end caps and Silver grey/white thermopainted Aluminum reflector with PMMA diffuser or I louvre/ 100% downlight.Available in 1x28w 2x28wT5 and 1x35 w and 2x35 T5 lamp options .	FTL5106-228	FTL5106-135	FTL5106-235
Model No									
FTL5106-128	Aluminum profile frame with aluminum reflector, ABS end caps and Silver grey/white thermopainted Aluminum reflector with PMMA diffuser or I louvre/ 100% downlight.Available in 1x28w 2x28wT5 and 1x35 w and 2x35 T5 lamp options .								
FTL5106-228									
FTL5106-135									
FTL5106-235									



	Moonlight Box	
	Model No	
	FTL5102-128	Aluminum profile frame with aluminum reflector Silver grey/ white thermopainted
	FTL 5102-135	5102 Model: Aluminum reflector with PMMA diffuser or I louvre/ 100% downlight
	FTL 5102-228	5102UD: Aluminum reflector with PMMA diffuser or I louvre/ 50% Uplight & 50% downlight
	FTL 5102-235	Available in 1x28w 2x28wT5 and 1x35 w and 2x35 T5 lamp options .
	FTL 5102UD-228	
	FTL5102UD-235	

	Element	Model No	
		FTL5117-414 PMMA	Housing of galvanised steel sheet, Frame made of aluminium & powdercoated Front diffuser in Out Bend Opal
		FTL5117-414 PMMA+I louver	PMMA Available in 4x14w T5 lamp option.



	Moonlight Box-Recess	Model No	
		FTL5108-128PMMA	Trimless luminaire housing of non deformable extruded aluminium, pure aluminum reflector & externally Silver grey/white thermopainted
		FTL5108-135PMMA	Aluminum reflector with PMMA diffuser or I louvre.
		FTL 5108 128 I LOUVRE	
		FTL 5108 135 I LOUVRE	

	Halo	Model No	
		PLL5126-236MB	Halo's unique lighting effect is achieved through a combination of optics and a lighting chamber. The direct optics increases the throughput of light while the indirect optic breaks up the lamp image perfectly. Various lamp options available .
		PLL5126-236EB	
		FTL5126-214	
		PLL5126-255MB	
		PLL5126-255EB	


	Quadra-Recess	Model No	
		FTL 5111-128	Highly-specular reflector, made of high-purity postanodised aluminium, for narrow/wide angle light distribution Micro-segmented parabolic louvre made of anodised aluminium with a surface purity of 99.98 %. Various lamp options available .
		FTL5111-228	
		FTL5112-314	
		FTL5112-414	

 	Quadra-Recess	Model No
		FTL5113-214
		FTL5111-236
		FTL5112-318
		FTL5112-418
		FTL5113-218


Bezel ring made of sheet steel, galvanised, powder-coated white, securely connected to the reflector. Recessed ceiling mounting by means of rapid-mounting springs. Perforated sheet separation in between in T5 range .

 	Quadra-Surface	Model No
		FTL5114-128
		FTL5114-228
		FTL5115-314
		FTL5115-414
		FTL5116-214
		FTL5114-136
		FTL5114-236
		FTL5115-318
		FTL5115-418
		FTL5116-218

Sololuce's surface mounted luminaires are made of sheet steel, galvanised, powder-coated white, securely connected to the reflector. Fixture comes in different size for T5 & T8 fixtures
Optical system:
Highly-specular reflector, made of high-purity postanodised aluminium, for narrow/wide angle light distribution
Micro-segmented parabolic louvre made of anodised aluminium with a surface purity of 99.98%.


	Stand I & Stand II	Model No
		FTL5118-255
		FTL5119-214

Made in aluminum extrusion profiles with PMMA diffuser.
Optics:
Stand I : 90% uplight+10% downlight
Stand II : 80% downlight + 20% uplight

	Bollard	Model No
		FTL 5109-128
		FTL5109-135

Made of aluminum extrusion profiles Bollard is available in two heights of 1500mm & 1800mm. Stand Body is Made in aluminum extrusion profiles with PMMA diffuser
Optics: Opal PMMA diffuser, forward light emission.

Perfetto



Model No

CFL5150-242 EB/MB	Perfetto from Sololuce is large family of downlights of high quality materials and advanced technical designs.
CFL5150-226 EB/MB	-Bodies, fixing systems and equipment boxes in
CFL5150-218 EB/MB	galvanized painted steel or polyamide re-enforced with
CFL5151-242 EB/MB	fibreglass.
CFL5151-226 EB/MB	-Reflectors of high purity anodized aluminium
CFL5151-218 EB/MB	All downlights have the option of :
CFL5154-242 EB/MB	Electromagnetic (MB) equipment in high power factor,
CFL5154-226 EB/MB	electronic (EB) equipment and dimmable electronic
CFL5154-218 EB/MB	equipment.
CFL5152-242 EB/MB	In version 1-10V and by push button or DALI included
CFL5152-226 EB/MB	according to the version. In models with symmetrical
CFL5152-218 EB/MB	horizontal optics for compact fluorescence, the equipment
CFL5153-242 E27	holding box is supplied attached in Integral models and
CFL5155-226 EB/MB	seperate in Non- Integral models .
CFL5155-218 EB/MB	Finished in colour: Black , white or grey.
CFL5155-213 EB/MB	
CFL5156-226 EB/MB	
CFL5156-218 EB/MB	
CFL5156-213 EB/MB	
CFL5157-226 E27	
CFL5159-126 E27	
CFL5158-118 E27	

Perfetto Polyamide









Model No


CFL 5162-213 EB-A/B/C/D	Bodies in polyamide re-enforced with
CFL 5163-226 EB-A/B/C/D	fibreglass & Reflectors of high purity anodized alu-
CFL 5163-218 EB-A/B/C/D	minium
CFL 5163-218 EB-A/B/C/D	ption


	Perfetto Polyamide Signora	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5236-113 EB/MB</td><td rowspan="7"><p>Bodies in polyamide re-enforced with fibreglass & Reflectors of Polycarbonate symmetric re- flector vacuum metalized with pure 99% aluminium powder</p><ul style="list-style-type: none">• Decorative ring at sight in technopolymer available in white, chrome and colour gold• Adjustable fixing bracket that guarantees a perfect fixing in the false ceiling (min. 4 max 33 mm)• G24/E27 lampholder and certified cabling• Also available without built in cable box</td></tr><tr><td>CFL 5236-118 EB/MB</td></tr><tr><td>CFL 5236-126EB/MB</td></tr><tr><td>CFL 5236-213EB/MB</td></tr><tr><td>CFL 5236 218 EB/MB</td></tr><tr><td>CFL 5236-226 EB/MB</td></tr><tr><td>CFL 5236 126 E27</td></tr><tr><td>CFL 5236 226 E27</td></tr></table>	Model No		CFL 5236-113 EB/MB	<p>Bodies in polyamide re-enforced with fibreglass & Reflectors of Polycarbonate symmetric re- flector vacuum metalized with pure 99% aluminium powder</p> <ul style="list-style-type: none">• Decorative ring at sight in technopolymer available in white, chrome and colour gold• Adjustable fixing bracket that guarantees a perfect fixing in the false ceiling (min. 4 max 33 mm)• G24/E27 lampholder and certified cabling• Also available without built in cable box	CFL 5236-118 EB/MB	CFL 5236-126EB/MB	CFL 5236-213EB/MB	CFL 5236 218 EB/MB	CFL 5236-226 EB/MB	CFL 5236 126 E27	CFL 5236 226 E27
Model No													
CFL 5236-113 EB/MB	<p>Bodies in polyamide re-enforced with fibreglass & Reflectors of Polycarbonate symmetric re- flector vacuum metalized with pure 99% aluminium powder</p> <ul style="list-style-type: none">• Decorative ring at sight in technopolymer available in white, chrome and colour gold• Adjustable fixing bracket that guarantees a perfect fixing in the false ceiling (min. 4 max 33 mm)• G24/E27 lampholder and certified cabling• Also available without built in cable box												
CFL 5236-118 EB/MB													
CFL 5236-126EB/MB													
CFL 5236-213EB/MB													
CFL 5236 218 EB/MB													
CFL 5236-226 EB/MB													
CFL 5236 126 E27													
CFL 5236 226 E27													
	Ellepta	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5177-120-E27</td><td rowspan="6"><p>Classic wall mounted elliptical luminaire adds visual structure to a simple form. Opal acrylic lens provides soft symmetrical distribution. Fixtures are completely made in pressure die cast aluminum in six different bezel options. All hardware is stainless steel. Standard colors; matte silver grey metallic or black. Special colors available.</p></td></tr><tr><td>CFL 5178-120-E27</td></tr><tr><td>CFL 5179-120-E27</td></tr><tr><td>CFL 5180-120-E27</td></tr><tr><td>CFL 5181-120-E27</td></tr><tr><td>CFL 5182-120-E27</td></tr></table>	Model No		CFL 5177-120-E27	<p>Classic wall mounted elliptical luminaire adds visual structure to a simple form. Opal acrylic lens provides soft symmetrical distribution. Fixtures are completely made in pressure die cast aluminum in six different bezel options. All hardware is stainless steel. Standard colors; matte silver grey metallic or black. Special colors available.</p>	CFL 5178-120-E27	CFL 5179-120-E27	CFL 5180-120-E27	CFL 5181-120-E27	CFL 5182-120-E27		
Model No													
CFL 5177-120-E27	<p>Classic wall mounted elliptical luminaire adds visual structure to a simple form. Opal acrylic lens provides soft symmetrical distribution. Fixtures are completely made in pressure die cast aluminum in six different bezel options. All hardware is stainless steel. Standard colors; matte silver grey metallic or black. Special colors available.</p>												
CFL 5178-120-E27													
CFL 5179-120-E27													
CFL 5180-120-E27													
CFL 5181-120-E27													
CFL 5182-120-E27													
	Orion	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL-5169 EB/MB-FC</td><td rowspan="6"><p>Orion is surface mounted simplistic design which brings character to the wall it is pasted on. A well accepted generic design fixture made of pressure die cast aluminum, now available in energy efficient CFL in two sizes 275mm and 220mm.</p></td></tr><tr><td>CFL-5169 EB/MB-HC</td></tr><tr><td>CFL-5169 EB/MB-GR</td></tr><tr><td>CFL-5167 EB/MB-FC</td></tr><tr><td>CFL-5167 EB/MB-HC</td></tr><tr><td>CFL-5167 EB/MB-GR</td></tr></table>	Model No		CFL-5169 EB/MB-FC	<p>Orion is surface mounted simplistic design which brings character to the wall it is pasted on. A well accepted generic design fixture made of pressure die cast aluminum, now available in energy efficient CFL in two sizes 275mm and 220mm.</p>	CFL-5169 EB/MB-HC	CFL-5169 EB/MB-GR	CFL-5167 EB/MB-FC	CFL-5167 EB/MB-HC	CFL-5167 EB/MB-GR		
Model No													
CFL-5169 EB/MB-FC	<p>Orion is surface mounted simplistic design which brings character to the wall it is pasted on. A well accepted generic design fixture made of pressure die cast aluminum, now available in energy efficient CFL in two sizes 275mm and 220mm.</p>												
CFL-5169 EB/MB-HC													
CFL-5169 EB/MB-GR													
CFL-5167 EB/MB-FC													
CFL-5167 EB/MB-HC													
CFL-5167 EB/MB-GR													
	Ovale	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5201-118 EB/MB-HC</td><td rowspan="6"><p>Pressure die cast aluminum body with opal polycarbonate lens . Pure silicon gaskets to provide IP54 protection and stainless steel screws and hardware. Fixture is cromate converted before powder coating . Mounting thru specially designed eyelids at back plate Application: Residential apartments, Hotels, Hospitals, Villas etc.</p></td></tr><tr><td>CFL 5201-118 EB/MB-FC</td></tr><tr><td>CFL 5201-118 EB/MB-GR</td></tr><tr><td>CFL 5202-118 EB/MB-HC</td></tr><tr><td>CFL 5202-118 EB/MB-FC</td></tr><tr><td>CFL 5202-118 EB/MB-GR</td></tr></table>	Model No		CFL 5201-118 EB/MB-HC	<p>Pressure die cast aluminum body with opal polycarbonate lens . Pure silicon gaskets to provide IP54 protection and stainless steel screws and hardware. Fixture is cromate converted before powder coating . Mounting thru specially designed eyelids at back plate Application: Residential apartments, Hotels, Hospitals, Villas etc.</p>	CFL 5201-118 EB/MB-FC	CFL 5201-118 EB/MB-GR	CFL 5202-118 EB/MB-HC	CFL 5202-118 EB/MB-FC	CFL 5202-118 EB/MB-GR		
Model No													
CFL 5201-118 EB/MB-HC	<p>Pressure die cast aluminum body with opal polycarbonate lens . Pure silicon gaskets to provide IP54 protection and stainless steel screws and hardware. Fixture is cromate converted before powder coating . Mounting thru specially designed eyelids at back plate Application: Residential apartments, Hotels, Hospitals, Villas etc.</p>												
CFL 5201-118 EB/MB-FC													
CFL 5201-118 EB/MB-GR													
CFL 5202-118 EB/MB-HC													
CFL 5202-118 EB/MB-FC													
CFL 5202-118 EB/MB-GR													


	Brik	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL-5168-218 EB/MB-FC</td><td rowspan="2">Brik, cleanline fixture which goes with the simple architecture, used for illuminating hallway, Villas, residential apartments, Hotels etc, can be used indoor as well as Outdoors. Made of pressure die cast aluminum with pure silicon gas-gaskets and ss hardware the fixture is available in 2X18w CFL.</td></tr><tr><td>CFL-5168-218 EB/MB-GR</td></tr></table>	Model No		CFL-5168-218 EB/MB-FC	Brik, cleanline fixture which goes with the simple architecture, used for illuminating hallway, Villas, residential apartments, Hotels etc, can be used indoor as well as Outdoors. Made of pressure die cast aluminum with pure silicon gas-gaskets and ss hardware the fixture is available in 2X18w CFL.	CFL-5168-218 EB/MB-GR	
Model No								
CFL-5168-218 EB/MB-FC	Brik, cleanline fixture which goes with the simple architecture, used for illuminating hallway, Villas, residential apartments, Hotels etc, can be used indoor as well as Outdoors. Made of pressure die cast aluminum with pure silicon gas-gaskets and ss hardware the fixture is available in 2X18w CFL.							
CFL-5168-218 EB/MB-GR								
	Alta	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5192-1x75/E27</td><td rowspan="2">Alta is a generic Polycarbonate wall/ceiling mount fixture . Simple yet elegant fixture. Multiple rings encircling the PC refractor allow a warm glow to radiate outward. Alta is suitable for Indoor and canopy area lighting</td></tr><tr><td>CFL5192-2X9MB</td></tr></table>	Model No		CFL 5192-1x75/E27	Alta is a generic Polycarbonate wall/ceiling mount fixture . Simple yet elegant fixture. Multiple rings encircling the PC refractor allow a warm glow to radiate outward. Alta is suitable for Indoor and canopy area lighting	CFL5192-2X9MB	
Model No								
CFL 5192-1x75/E27	Alta is a generic Polycarbonate wall/ceiling mount fixture . Simple yet elegant fixture. Multiple rings encircling the PC refractor allow a warm glow to radiate outward. Alta is suitable for Indoor and canopy area lighting							
CFL5192-2X9MB								
	Bella	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5193-1x75E27</td><td rowspan="2">Wall or Ceiling mount Bella creates beautiful effects. Opal PC refractor radiates glarefree light. Completely made of no yellowing polycarbonate, Bella is suitable for indoor / canopy applications.</td></tr><tr><td>CFL5193-2X9MB</td></tr></table>	Model No		CFL 5193-1x75E27	Wall or Ceiling mount Bella creates beautiful effects. Opal PC refractor radiates glarefree light. Completely made of no yellowing polycarbonate, Bella is suitable for indoor / canopy applications.	CFL5193-2X9MB	
Model No								
CFL 5193-1x75E27	Wall or Ceiling mount Bella creates beautiful effects. Opal PC refractor radiates glarefree light. Completely made of no yellowing polycarbonate, Bella is suitable for indoor / canopy applications.							
CFL5193-2X9MB								
	Tonda	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5194-1x75E27</td><td rowspan="2">The contemporary styling of Tonda presents a striking accent to classical architecture. Translucent PC lens minimize dayform mass while subtly refracting light at night. Completely made of no yellowing polycarbonate, Tonda is suitable for indoor / canopy applications.</td></tr><tr><td>CFL5194-2X9MB</td></tr></table>	Model No		CFL 5194-1x75E27	The contemporary styling of Tonda presents a striking accent to classical architecture. Translucent PC lens minimize dayform mass while subtly refracting light at night. Completely made of no yellowing polycarbonate, Tonda is suitable for indoor / canopy applications.	CFL5194-2X9MB	
Model No								
CFL 5194-1x75E27	The contemporary styling of Tonda presents a striking accent to classical architecture. Translucent PC lens minimize dayform mass while subtly refracting light at night. Completely made of no yellowing polycarbonate, Tonda is suitable for indoor / canopy applications.							
CFL5194-2X9MB								
	Samussa	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5195-1X100W E27</td><td rowspan="3">Samussa is ceiling / Wall mounted fixture required at places where little high light levels are required. Suitable to accept upto 2x18w CFL. Completely made of no yellowing polycarbonate, Samussa is suitable for indoor / canopy applications.</td></tr><tr><td>CFL 5195-2X13MB</td></tr><tr><td>CFL 5195-2X18MB</td></tr></table>	Model No		CFL 5195-1X100W E27	Samussa is ceiling / Wall mounted fixture required at places where little high light levels are required. Suitable to accept upto 2x18w CFL. Completely made of no yellowing polycarbonate, Samussa is suitable for indoor / canopy applications.	CFL 5195-2X13MB	CFL 5195-2X18MB
Model No								
CFL 5195-1X100W E27	Samussa is ceiling / Wall mounted fixture required at places where little high light levels are required. Suitable to accept upto 2x18w CFL. Completely made of no yellowing polycarbonate, Samussa is suitable for indoor / canopy applications.							
CFL 5195-2X13MB								
CFL 5195-2X18MB								
	Moon	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5205-118 EB/MB</td><td>Moon is a fitting that was born to light and enhance surfaces, details, and residential areas. A ceiling-mounting system for decorative lighting effects. Moon has been designed with innovative technologies and distributes the light flow evenly. Available in 18w CFL version.</td></tr></table>	Model No		CFL 5205-118 EB/MB	Moon is a fitting that was born to light and enhance surfaces, details, and residential areas. A ceiling-mounting system for decorative lighting effects. Moon has been designed with innovative technologies and distributes the light flow evenly. Available in 18w CFL version.		
Model No								
CFL 5205-118 EB/MB	Moon is a fitting that was born to light and enhance surfaces, details, and residential areas. A ceiling-mounting system for decorative lighting effects. Moon has been designed with innovative technologies and distributes the light flow evenly. Available in 18w CFL version.							
	Vivo	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5203-118 E27</td><td>Vivo made of pressure die cast aluminum with Opal PC lens. Its application is most suitable for Exterior Villa lighting, security lighting, Hallway, Hotels or simply as tall bollard.</td></tr></table>	Model No		CFL 5203-118 E27	Vivo made of pressure die cast aluminum with Opal PC lens. Its application is most suitable for Exterior Villa lighting, security lighting, Hallway, Hotels or simply as tall bollard.		
Model No								
CFL 5203-118 E27	Vivo made of pressure die cast aluminum with Opal PC lens. Its application is most suitable for Exterior Villa lighting, security lighting, Hallway, Hotels or simply as tall bollard.							



	Cubo	<p>Model No</p> <p>CFL 5204-111 A wall-mounted model featuring a subtle and essential design. This luminaire supplies effective lighting wherever an effect of soft elegance is required. Pressure die cast housing with silicon gaskets and PC lens in IP54 ingress protection make it ideal for indoor as well as outdoor application.</p>
	Punto	<p>Model No</p> <p>CFL 5207-126 EB/MB The clean and linear design of the Punto has been developed with an eye to smoothly lighting surrounding surfaces. Fixture produced in die cast aluminium, with PC lens fixture offers right solution for Interior exterior area lighting and landscape lighting or pathways .</p>
	Quanto	<p>Model No</p> <p>CFL 5206-126EB/MB Produced in sturdy, long-lasting aluminum die cast , they are equipped with high-performance, optics to optimize lamp performance and lower operating costs. Fixture with diffused PC optics is suitable both for accent and diffuse lighting of walking and transit ways.</p>
	Nova	<p>Model No</p> <p>CFL-5210-118 MB/EB Made in aluminum with polycarbonate lens, Nova supports highly efficient 18w CFL.</p> <p>CFL-5211-118 MB/EB Fixture is available in wall mount and base mount models and suitable for Villas , landscapes, hotels, entertainment places etc..</p> <p>CFL-5212-118 MB/EB</p>
	EasyLux	<p>Model No</p> <p>FTL5122-236 Opal Transparencies that allow light to go through the luminaire, enveloping it and thus integrating it into the place. This is the essence of the new series EasyLux . The fact that the luminaire body is translucent allows playing with the opal sheets that set at different places inside the luminaire send the light out onto the area intended, resulting in two basic models: a Prismatic model, and an opal model. All models can be surface mounted to either ceiling or walls .Bodies in white painted galvanized steel, Diffusers of PMMA in Opal, Prismatic.</p> <p>FTL5122-236 Prismatic</p> <p>FTL5124-218 Opal</p> <p>FTL5124-218 Prismatic</p> <p>FTL5125-236 Opal</p> <p>FTL5125-236 Prismatic</p> <p>FTL5125 (S)-136 Available in 2x36w/2x28w /1x36w lamp options .</p>


Policar		Model No
	FTL 5170-118	Manufactured in compressed polyester reinforced with fibre glass , with dished clear polycarbonate cover.
	FTL 5171-218	Polyurethane gasket to guarantee an IP 66 rating.Suitable for use in multi-storey car parks, changing areas and
	FTL 5172-136	factories, plant rooms, loading bays , construction sites.
	FTL 5173-236	chemically aggressive or corrosive atmospheres e.g. road
	FTL 5174-128	/ rail tunnels, chemical and oil production plants, marine
	FTL5175 -228	/ coastal type environments, galvanic treatment areas, livestock, abattoirs and food industries.


Policar Plus		Model No
	FTL 5184-118EB	Waterproof fittings suitable for civil, commercial, industrial and public areas where is demanded protection against dust and
	FTL 5185-218EB	moisture. Housing is made of polycarbonate with high degree of impact resistance. Silicon anti-ageing sealing gasket. Protection
	FTL 5186-136EB	tube made of in transparent polycarbonate smooth finished and dust protected unbreakable and self-extinguishing Electronic
	FTL 5187-236EB	ballast standard for Policar Plus


Stagna New		Model No
	FTL 5230-118 EB/MB	The Stagna™ are with specially designed PC refractor to give architects a better choce over the standard
	FTL 5231-218 EB/MB	box typr weatherproof fixture, strictly complying the standards. Stagna are robust IP66 corrosion resistant, moisture
	FTL 5232 136 EB/MB	and dust proof fittings for industrial type applications, suitable for use with T8 and T5 fluorescent lamps to provide high
	FTL 5233 236 EB/MB	performance efficient lighting. Manufactured in compressed polyester reinforced with fibre glass , with designer clear poly-
	FTL 5234 128 EB	carbonate cover.
	FTL 5235 228 EB	

Inductalux		Model No
	IND 5221-40	Practically maintenance-free, induction lighting offers many features that make it an attractive light source and is emerging as one of the newest technologies in lighting. With a 100,000 hour rated life, these systems seldom need replacing. Particularly useful in applications where lamp replacement is cumbersome and expensive, as in some outdoor applications and in hard-to-reach areas such as tunnels, airports, public facilities, freezers, and many others.
	IND 5221-60	
	IND 5221-80	
	IND 5221-100	
	IND 5221-120	
	IND 5221-150	
	IND 5221-200	
	IND 5221-250	
	IND 5221-300	

	Inductalux	<table><tr><th colspan="2">Model No</th></tr><tr><td>IND 5222-40</td><td rowspan="8"></td></tr><tr><td>IND 5222-60</td></tr><tr><td>IND 5222-80</td></tr><tr><td>IND 5222-100</td></tr><tr><td>IND 5222-120</td></tr><tr><td>IND 5222-150</td></tr><tr><td>IND 5222-200</td></tr><tr><td>IND 5222-250</td></tr><tr><td>IND 5222-300</td><td></td></tr></table>	Model No		IND 5222-40		IND 5222-60	IND 5222-80	IND 5222-100	IND 5222-120	IND 5222-150	IND 5222-200	IND 5222-250	IND 5222-300	
Model No															
IND 5222-40															
IND 5222-60															
IND 5222-80															
IND 5222-100															
IND 5222-120															
IND 5222-150															
IND 5222-200															
IND 5222-250															
IND 5222-300															
	Battens	<table><tr><th colspan="2">Model No</th></tr><tr><td>FTL 5188-136</td><td rowspan="4">Heavy duty industrial Batten for 28Watt T5 and 36 Watt T8 fluorescent lamp . The Batten is made form CRCA sheet steel powder coated gray and white cover. The reflector can be either powder coated or sandwiched aluminium. Batten family is a range of robust industrial solutions suitable for lighting general industrial spaces like panel rooms, switch gear rooms etc.</td></tr><tr><td>FTL 5189-236</td></tr><tr><td>FTL 5190-128</td></tr><tr><td>FTL 5191-228</td></tr></table>	Model No		FTL 5188-136	Heavy duty industrial Batten for 28Watt T5 and 36 Watt T8 fluorescent lamp . The Batten is made form CRCA sheet steel powder coated gray and white cover. The reflector can be either powder coated or sandwiched aluminium. Batten family is a range of robust industrial solutions suitable for lighting general industrial spaces like panel rooms, switch gear rooms etc.	FTL 5189-236	FTL 5190-128	FTL 5191-228						
Model No															
FTL 5188-136	Heavy duty industrial Batten for 28Watt T5 and 36 Watt T8 fluorescent lamp . The Batten is made form CRCA sheet steel powder coated gray and white cover. The reflector can be either powder coated or sandwiched aluminium. Batten family is a range of robust industrial solutions suitable for lighting general industrial spaces like panel rooms, switch gear rooms etc.														
FTL 5189-236															
FTL 5190-128															
FTL 5191-228															
	Linea	<table><tr><th colspan="2">Model No</th></tr><tr><td>FTL 5165-14</td><td rowspan="2">Linea is a complete system, which, via technologically evolved T5 Lamp , is able to adapt itself to the most diverse architecture: building exteriors, and buildings, details, facades, etc.. Made of extruded aluminum with tempered glass in IP67 ingress protection , Silicon gaskets & Galvanized gear plate</td></tr><tr><td>FTL 5166-28</td></tr></table>	Model No		FTL 5165-14	Linea is a complete system, which, via technologically evolved T5 Lamp , is able to adapt itself to the most diverse architecture: building exteriors, and buildings, details, facades, etc.. Made of extruded aluminum with tempered glass in IP67 ingress protection , Silicon gaskets & Galvanized gear plate	FTL 5166-28								
Model No															
FTL 5165-14	Linea is a complete system, which, via technologically evolved T5 Lamp , is able to adapt itself to the most diverse architecture: building exteriors, and buildings, details, facades, etc.. Made of extruded aluminum with tempered glass in IP67 ingress protection , Silicon gaskets & Galvanized gear plate														
FTL 5166-28															
	Classique	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5240-142 E27</td><td rowspan="2">Classique range offers solutions for architectural buildings or villas which have been designed considering country's culture and values.</td></tr><tr><td>CFL 5241-142 E27</td></tr><tr><td>CFL 5242-242 E27</td><td rowspan="2">Made of cast aluminum, silicon seals, embellishments and hard glass, fixtures offer longlasting solutions.</td></tr><tr><td>CFL 5243-242 E27</td></tr></table>	Model No		CFL 5240-142 E27	Classique range offers solutions for architectural buildings or villas which have been designed considering country's culture and values.	CFL 5241-142 E27	CFL 5242-242 E27	Made of cast aluminum, silicon seals, embellishments and hard glass, fixtures offer longlasting solutions.	CFL 5243-242 E27					
Model No															
CFL 5240-142 E27	Classique range offers solutions for architectural buildings or villas which have been designed considering country's culture and values.														
CFL 5241-142 E27															
CFL 5242-242 E27	Made of cast aluminum, silicon seals, embellishments and hard glass, fixtures offer longlasting solutions.														
CFL 5243-242 E27															
	Acrylux	<table><tr><th colspan="2">Model No</th></tr><tr><td>CFL 5220-100 E27</td><td>Classique range offers solutions for architectural buildings or villas Made of simple acrylic refractors in ceiling mount option .</td></tr></table>	Model No		CFL 5220-100 E27	Classique range offers solutions for architectural buildings or villas Made of simple acrylic refractors in ceiling mount option .									
Model No															
CFL 5220-100 E27	Classique range offers solutions for architectural buildings or villas Made of simple acrylic refractors in ceiling mount option .														

	Bagno
Model No	
FTL 5225-20	Bagno is general application lighting fixtures available in engineered plastic , sheet metal aluminum extrusion profiles. Standard models are in T5/T8 fluorescent tubes but option of LED tubes also available.
FTL 5226-40	
FTL 5227-13	


	<h1>O₂</h1>	<table><tr><th colspan="2">Model No</th></tr><tr><td>FTL 5245-2X55 C</td><td rowspan="6"><p>O2 lighting system is a range of products designed for T5 circular fluorescent lamps. It offers diffused lighting with high and efficient lumen output. Die casting silver paint body and metachrilate transparent shade. Wide range of shade colors. The several possible colors ombination able different uses in any application where high lumen performance and modern style concept are requested. Suspended lamps, table, wall and ceiling application complete our offer. Electronic feeding by electronic device to combine high quality standard with the lowest electric consumption.</p></td></tr><tr><td>FTL 5245-2X55 W</td></tr><tr><td>FTL 5245-2X55 H</td></tr><tr><td>FTL 5246-1X55 C</td></tr><tr><td>FTL 5246-1X55 W</td></tr><tr><td>FTL 5246-1X55 H</td></tr><tr><td>FTL 5246-1X55 D</td><td></td></tr></table>	Model No		FTL 5245-2X55 C	<p>O2 lighting system is a range of products designed for T5 circular fluorescent lamps. It offers diffused lighting with high and efficient lumen output. Die casting silver paint body and metachrilate transparent shade. Wide range of shade colors. The several possible colors ombination able different uses in any application where high lumen performance and modern style concept are requested. Suspended lamps, table, wall and ceiling application complete our offer. Electronic feeding by electronic device to combine high quality standard with the lowest electric consumption.</p>	FTL 5245-2X55 W	FTL 5245-2X55 H	FTL 5246-1X55 C	FTL 5246-1X55 W	FTL 5246-1X55 H	FTL 5246-1X55 D	
Model No													
FTL 5245-2X55 C	<p>O2 lighting system is a range of products designed for T5 circular fluorescent lamps. It offers diffused lighting with high and efficient lumen output. Die casting silver paint body and metachrilate transparent shade. Wide range of shade colors. The several possible colors ombination able different uses in any application where high lumen performance and modern style concept are requested. Suspended lamps, table, wall and ceiling application complete our offer. Electronic feeding by electronic device to combine high quality standard with the lowest electric consumption.</p>												
FTL 5245-2X55 W													
FTL 5245-2X55 H													
FTL 5246-1X55 C													
FTL 5246-1X55 W													
FTL 5246-1X55 H													
FTL 5246-1X55 D													


Luna	Model No	
	<p>CFL 5208-122 T5 Circline</p> <p>CFL 5208-128 T5 Circline</p> <p>CFL 5208-128 2D</p> <p>CFL 5208-132 2D</p> <p>CFL 5208-226 PLC/EB</p> <p>CFL 5209-132 T5 Circline</p> <p>CFL 5209-140 T5 Circline</p> <p>CFL 5209-155 T5 Circline</p> <p>CFL 5209-155 2D</p> <p>CFL 5209-326 PLC/EB</p>	<p>Simplistic Luna hides the most intricate electronic inside. Intelligent Heat dissipation designed without destroying the beauty of luminaire. Surface mounted Polycarbonate fixture suitable for car parks, Halls, Foyers and Hypermarkets. Available in two sizes of 300mm and 350mm with CFL/ Circline & 2D lamp options. Clear/opal polycarbonate cover option available</p>

HID Lighting


Sololuce HID Lighting








	Colline	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6107-250</td><td rowspan="3">The avant-garde housing is available with flat glass. Extremely rugged, high grade diecast aluminium, in two surface finishes; Black & Grey. Fixture uses high grade aluminum reflector for perfect batwing street optics, and completely complies with IP66 requirements for optical and control gear requirements and comes with engineered plastic control gear tray for achieving class II requirements.</td></tr><tr><td>HID 6107-400</td></tr><tr><td>HID 6107-600</td></tr></table>	Model No		HID 6107-250	The avant-garde housing is available with flat glass. Extremely rugged, high grade diecast aluminium, in two surface finishes; Black & Grey. Fixture uses high grade aluminum reflector for perfect batwing street optics, and completely complies with IP66 requirements for optical and control gear requirements and comes with engineered plastic control gear tray for achieving class II requirements.	HID 6107-400	HID 6107-600				
Model No												
HID 6107-250	The avant-garde housing is available with flat glass. Extremely rugged, high grade diecast aluminium, in two surface finishes; Black & Grey. Fixture uses high grade aluminum reflector for perfect batwing street optics, and completely complies with IP66 requirements for optical and control gear requirements and comes with engineered plastic control gear tray for achieving class II requirements.											
HID 6107-400												
HID 6107-600												
	Munza	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6108-35-PGj5</td><td rowspan="4">The avant-garde housing is available with flat glass and in Drop Glass. Extremely rugged in high grade diecast aluminium. Fixture uses high grade aluminum reflector for perfect batwing street optics, all hardware is of stainless steel and is externally powder coated after cromate conversion. Luminare completely complies with IP66 requirements for optical and control gear requirements and comes with engineered plastic control gear tray for achieving class II requirements.</td></tr><tr><td>HID 6108-70-G12/G27</td></tr><tr><td>HID 6108-100-G12/G27</td></tr><tr><td>HID 6108-150-G12/G27</td></tr></table>	Model No		HID 6108-35-PGj5	The avant-garde housing is available with flat glass and in Drop Glass. Extremely rugged in high grade diecast aluminium. Fixture uses high grade aluminum reflector for perfect batwing street optics, all hardware is of stainless steel and is externally powder coated after cromate conversion. Luminare completely complies with IP66 requirements for optical and control gear requirements and comes with engineered plastic control gear tray for achieving class II requirements.	HID 6108-70-G12/G27	HID 6108-100-G12/G27	HID 6108-150-G12/G27			
Model No												
HID 6108-35-PGj5	The avant-garde housing is available with flat glass and in Drop Glass. Extremely rugged in high grade diecast aluminium. Fixture uses high grade aluminum reflector for perfect batwing street optics, all hardware is of stainless steel and is externally powder coated after cromate conversion. Luminare completely complies with IP66 requirements for optical and control gear requirements and comes with engineered plastic control gear tray for achieving class II requirements.											
HID 6108-70-G12/G27												
HID 6108-100-G12/G27												
HID 6108-150-G12/G27												
	Velocity	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6101- 250/400-ET</td><td rowspan="2">Designed with sober and timeless shapes, Velocity , brings life to Urban Areas and Roads . Fixture made in pressure die cast with two models available one with decorative extended top (ET)and one with short top (ST)</td></tr><tr><td>HID 6101-250/400-ST</td></tr></table>	Model No		HID 6101- 250/400-ET	Designed with sober and timeless shapes, Velocity , brings life to Urban Areas and Roads . Fixture made in pressure die cast with two models available one with decorative extended top (ET)and one with short top (ST)	HID 6101-250/400-ST					
Model No												
HID 6101- 250/400-ET	Designed with sober and timeless shapes, Velocity , brings life to Urban Areas and Roads . Fixture made in pressure die cast with two models available one with decorative extended top (ET)and one with short top (ST)											
HID 6101-250/400-ST												
	Oliver	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6105-70</td><td rowspan="3">Two luminaire sizes are available to meet proportional requirements of large or small scale applications. The heavy pressure die cast aluminum housing is fitted with a tempered glass lens with single clamp for easy relamping. Fully closed reflector assembly with easy access to the ballast tray.</td></tr><tr><td>HID 6105-150</td></tr><tr><td>HID 6105-250</td></tr><tr><td>HID 6105-400</td><td rowspan="3">Two models available one upto 600w and other upto 400w.</td></tr><tr><td>HID 6106 -400</td></tr><tr><td>HID 6106-600</td></tr></table>	Model No		HID 6105-70	Two luminaire sizes are available to meet proportional requirements of large or small scale applications. The heavy pressure die cast aluminum housing is fitted with a tempered glass lens with single clamp for easy relamping. Fully closed reflector assembly with easy access to the ballast tray.	HID 6105-150	HID 6105-250	HID 6105-400	Two models available one upto 600w and other upto 400w.	HID 6106 -400	HID 6106-600
Model No												
HID 6105-70	Two luminaire sizes are available to meet proportional requirements of large or small scale applications. The heavy pressure die cast aluminum housing is fitted with a tempered glass lens with single clamp for easy relamping. Fully closed reflector assembly with easy access to the ballast tray.											
HID 6105-150												
HID 6105-250												
HID 6105-400	Two models available one upto 600w and other upto 400w.											
HID 6106 -400												
HID 6106-600												







TriLume		Model No
	HID 6107-250	<p>The TriLume series timeless styling blends with a broad range of architecture. Three sizes are available to meet diverse proportional requirements. This Trilume series fulfils the requirements of lighting Roads , Squares and Public spaces for pedestrians, guaranteeing maximum visual comfort and at the same time a piece of urban furnishing which is an expression of contemporary design. Corrosion resistant die-cast aluminium body, IP66 ingress Protection, tempered drop glass, AISI 304 stainless steel hardware, silicone rubber gaskets, polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment) and 60mm dia pole inlet</p> <p>Options :</p> <p>Two sizes , each having three variants</p> <p>Top Pole Mount (TM)</p> <p>Side Pole Mount (SM)</p> <p>Bracket Pole Mount (BM)</p>
	HID 6107-400	
	HID 6107-600	
	HID 6107-250	
	HID 6107-400	
	HID 6107-600	
	HID 6107-250	
	HID 6107-400	
	HID 6107-600	






	Esplanda	Model No	
	HID 6117-70 G12	One luminaire available for HID lamp or energy saving PLL lamp creates a unique visual accent. The sleek housing and door-frame are heavy-duty die cast aluminum with heat dissipation	
	HID 6117-150 G12	fins at the backside. Clear impact resistant tempered glass lens and horizontal lamp reflector provides effective illumination.	
	HID 6117-48 PLL		

	Square	Model No	
	HID 6129-250 SF	<p>SQUARE are a range of high performance compact Street cum floodlights The SQUARE range is available for lamps up to 400W.Suitable for following light distribution:</p> <ul style="list-style-type: none">- symmetrical / asymmetrical medium beam for tennis court lighting / street lighting	
	HID 6129-400 SF		
	HID 6130-250 PM		
	HID 6130-400 PM		

	Marte	Model No	
	HID 6162-150	Pressure Die cast aluminum housing with textured powdercoat finish over a chromate conversion coating with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern for maximum pole spacing. with Tempered Curved glass lens	
	HID 6162-250		
	HID 6162-400		

	Marte Plus	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6163-70</td><td rowspan="4">Pressure Die cast aluminum housing with textured powdercoat finish over a chromate conversion coating with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern for maximum pole spacing. Tempered Curved /flat glass lens</td></tr><tr><td>HID 6163-150</td></tr><tr><td>HID 6164-250</td></tr><tr><td>HID 6164-400</td></tr></table>	Model No		HID 6163-70	Pressure Die cast aluminum housing with textured powdercoat finish over a chromate conversion coating with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern for maximum pole spacing. Tempered Curved /flat glass lens	HID 6163-150	HID 6164-250	HID 6164-400
Model No									
HID 6163-70	Pressure Die cast aluminum housing with textured powdercoat finish over a chromate conversion coating with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern for maximum pole spacing. Tempered Curved /flat glass lens								
HID 6163-150									
HID 6164-250									
HID 6164-400									
	Marte-Element	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6165-150</td><td rowspan="2">Pressure Die cast aluminum housing with textured powdercoat finish over a chromate conversion coating with hinged top & lens frame. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern for maximum pole spacing & flat tempered glass</td></tr><tr><td>HID 6165-250</td></tr></table>	Model No		HID 6165-150	Pressure Die cast aluminum housing with textured powdercoat finish over a chromate conversion coating with hinged top & lens frame. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern for maximum pole spacing & flat tempered glass	HID 6165-250		
Model No									
HID 6165-150	Pressure Die cast aluminum housing with textured powdercoat finish over a chromate conversion coating with hinged top & lens frame. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern for maximum pole spacing & flat tempered glass								
HID 6165-250									
	Marte-Line	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6166-250</td><td rowspan="2">Pressure Die cast aluminum housing with textured powdercoat with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern Tempered Curved glass lens</td></tr><tr><td>HID 6166-400</td></tr></table>	Model No		HID 6166-250	Pressure Die cast aluminum housing with textured powdercoat with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern Tempered Curved glass lens	HID 6166-400		
Model No									
HID 6166-250	Pressure Die cast aluminum housing with textured powdercoat with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern Tempered Curved glass lens								
HID 6166-400									
	Marte Sigma	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6167-150</td><td rowspan="2">Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern . Tempered Curved/Flat glass lens</td></tr><tr><td>HID 6167-250</td></tr></table>	Model No		HID 6167-150	Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern . Tempered Curved/Flat glass lens	HID 6167-250		
Model No									
HID 6167-150	Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. Reflector: High efficiency one piece extra wide beam pattern . Tempered Curved/Flat glass lens								
HID 6167-250									
	Marte Zigma	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6168-150</td><td rowspan="2">Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. High efficiency one piece extra wide beam pattern for maximum pole spacing.. Tempered Curved/Flat glass lens</td></tr><tr><td>HID 6168-250</td></tr></table>	Model No		HID 6168-150	Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. High efficiency one piece extra wide beam pattern for maximum pole spacing.. Tempered Curved/Flat glass lens	HID 6168-250		
Model No									
HID 6168-150	Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for vertical & horizontal mounting. High efficiency one piece extra wide beam pattern for maximum pole spacing.. Tempered Curved/Flat glass lens								
HID 6168-250									
	Marte-Trend	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6169-70</td><td rowspan="4">Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for horizontal mounting. High efficiency one piece extra wide beam pattern for maximum pole spacing. Tempered Curved glass lens</td></tr><tr><td>HID 6169-150</td></tr><tr><td>HID 6170-250</td></tr><tr><td>HID 6170-400</td></tr></table>	Model No		HID 6169-70	Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for horizontal mounting. High efficiency one piece extra wide beam pattern for maximum pole spacing. Tempered Curved glass lens	HID 6169-150	HID 6170-250	HID 6170-400
Model No									
HID 6169-70	Pressure Die cast aluminum housing with textured powdercoat finish with hinged top & lens frame. SS clips for easy maintenance. Suitable for horizontal mounting. High efficiency one piece extra wide beam pattern for maximum pole spacing. Tempered Curved glass lens								
HID 6169-150									
HID 6170-250									
HID 6170-400									
	Hermis	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6104-70</td><td rowspan="2">Hermis is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.</td></tr><tr><td>HID 6104-150</td></tr></table>	Model No		HID 6104-70	Hermis is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.	HID 6104-150		
Model No									
HID 6104-70	Hermis is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.								
HID 6104-150									

	Sirrus	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6102-70</td><td rowspan="2">Sirrus is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.</td></tr><tr><td>HID 6102-150</td></tr></table>	Model No		HID 6102-70	Sirrus is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.	HID 6102-150				
Model No											
HID 6102-70	Sirrus is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.										
HID 6102-150											
	Krypton	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6103-70A</td><td rowspan="6">Krypton combines exceptional design with modern technology and is the ideal solution for walkways, parks and squares. It complements its location to give a unique atmosphere. Krypton is designed to be pole top mounted on 4 to 5m columns using the slip over mounting sleeve of 85mm Spigot entry. Krypton is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.</td></tr><tr><td>HID 6103-150A</td></tr><tr><td>HID 6103-70B</td></tr><tr><td>HID 6103-150B</td></tr><tr><td>HID 6103-70C</td></tr><tr><td>HID 6103-150C</td></tr></table>	Model No		HID 6103-70A	Krypton combines exceptional design with modern technology and is the ideal solution for walkways, parks and squares. It complements its location to give a unique atmosphere. Krypton is designed to be pole top mounted on 4 to 5m columns using the slip over mounting sleeve of 85mm Spigot entry. Krypton is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.	HID 6103-150A	HID 6103-70B	HID 6103-150B	HID 6103-70C	HID 6103-150C
Model No											
HID 6103-70A	Krypton combines exceptional design with modern technology and is the ideal solution for walkways, parks and squares. It complements its location to give a unique atmosphere. Krypton is designed to be pole top mounted on 4 to 5m columns using the slip over mounting sleeve of 85mm Spigot entry. Krypton is made of die cast aluminum body with Polycarbonate vandal resistant lens Thermally tested and suitable for upto 150w HID lamps, IP66 ingress Protection, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.										
HID 6103-150A											
HID 6103-70B											
HID 6103-150B											
HID 6103-70C											
HID 6103-150C											
	Globus	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6110-70</td><td rowspan="2">Globus is corrosion resistant die-cast aluminium body with hydroformed aluminum reflector , IP66 ingress Protection Tempered flat glass , AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.</td></tr><tr><td>HID 6110-150</td></tr></table>	Model No		HID 6110-70	Globus is corrosion resistant die-cast aluminium body with hydroformed aluminum reflector , IP66 ingress Protection Tempered flat glass , AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.	HID 6110-150				
Model No											
HID 6110-70	Globus is corrosion resistant die-cast aluminium body with hydroformed aluminum reflector , IP66 ingress Protection Tempered flat glass , AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating.										
HID 6110-150											
	Pelican	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6109-70</td><td rowspan="2">Pelican corrosion resistant die-cast aluminium body with spun aluminum shade , IP66 ingress Protection, PC diffuser, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating .</td></tr><tr><td>HID 6109-150</td></tr></table>	Model No		HID 6109-70	Pelican corrosion resistant die-cast aluminium body with spun aluminum shade , IP66 ingress Protection, PC diffuser, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating .	HID 6109-150				
Model No											
HID 6109-70	Pelican corrosion resistant die-cast aluminium body with spun aluminum shade , IP66 ingress Protection, PC diffuser, AISI 304 stainless steel hardware, silicone rubber gaskets & polyester powder coating .										
HID 6109-150											
	Berlin	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6141-150</td><td rowspan="3">The Fibreglass reinforced engineered plastic housing and acrylic refractor with integrated pole top fitter anchors rods to support the flat spun aluminum top cap. All hardware is stainless steel. Luminaire is available in 150W/250W and 400W HPS high pressure sodium/MH metal halide lamp.</td></tr><tr><td>HID 6141-250</td></tr><tr><td>HID 6141-400</td></tr></table>	Model No		HID 6141-150	The Fibreglass reinforced engineered plastic housing and acrylic refractor with integrated pole top fitter anchors rods to support the flat spun aluminum top cap. All hardware is stainless steel. Luminaire is available in 150W/250W and 400W HPS high pressure sodium/MH metal halide lamp.	HID 6141-250	HID 6141-400			
Model No											
HID 6141-150	The Fibreglass reinforced engineered plastic housing and acrylic refractor with integrated pole top fitter anchors rods to support the flat spun aluminum top cap. All hardware is stainless steel. Luminaire is available in 150W/250W and 400W HPS high pressure sodium/MH metal halide lamp.										
HID 6141-250											
HID 6141-400											
	Madrid	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6138-70</td><td>Luminaires are made of Fibreglass reinforced engineered plastic with excellent impact resistance upto IK10.</td></tr><tr><td>HID 6138-150</td><td rowspan="3">The diffuser lens is made of high efficiency non- yellowing acrylic with insde reflector and canopy made of aluminum. Luminaire is available in 70W//150W HPS high pressure sodium, /MH metal halide lamp.</td></tr><tr><td>HID 6139-70</td></tr><tr><td>HID 6139-150</td></tr></table>	Model No		HID 6138-70	Luminaires are made of Fibreglass reinforced engineered plastic with excellent impact resistance upto IK10.	HID 6138-150	The diffuser lens is made of high efficiency non- yellowing acrylic with insde reflector and canopy made of aluminum. Luminaire is available in 70W//150W HPS high pressure sodium, /MH metal halide lamp.	HID 6139-70	HID 6139-150	
Model No											
HID 6138-70	Luminaires are made of Fibreglass reinforced engineered plastic with excellent impact resistance upto IK10.										
HID 6138-150	The diffuser lens is made of high efficiency non- yellowing acrylic with insde reflector and canopy made of aluminum. Luminaire is available in 70W//150W HPS high pressure sodium, /MH metal halide lamp.										
HID 6139-70											
HID 6139-150											

	Oslo	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6140-70</td><td rowspan="2">The Fibreglass reinforced engineered plastic housing with integrated pole top fitter and flat spun aluminum top cap. All hardware is stainless steel. Luminaire is available in 70W//150W HPS high pressure sodium/MH metal halide lamp.</td></tr><tr><td>HID 6140-150</td></tr></table>	Model No		HID 6140-70	The Fibreglass reinforced engineered plastic housing with integrated pole top fitter and flat spun aluminum top cap. All hardware is stainless steel. Luminaire is available in 70W//150W HPS high pressure sodium/MH metal halide lamp.	HID 6140-150										
Model No																	
HID 6140-70	The Fibreglass reinforced engineered plastic housing with integrated pole top fitter and flat spun aluminum top cap. All hardware is stainless steel. Luminaire is available in 70W//150W HPS high pressure sodium/MH metal halide lamp.																
HID 6140-150																	
	IDUS	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6195-70G12</td><td rowspan="2">IDUS is made in corrosion free extrusion aluminium and vandal resistant PC or tempered glass , giving it superior durability. It is available in height of 3.8m in powder coated black as standard but other non standard RAL colours available on request .</td></tr><tr><td>HID 6195-150G12</td></tr></table>	Model No		HID 6195-70G12	IDUS is made in corrosion free extrusion aluminium and vandal resistant PC or tempered glass , giving it superior durability. It is available in height of 3.8m in powder coated black as standard but other non standard RAL colours available on request .	HID 6195-150G12										
Model No																	
HID 6195-70G12	IDUS is made in corrosion free extrusion aluminium and vandal resistant PC or tempered glass , giving it superior durability. It is available in height of 3.8m in powder coated black as standard but other non standard RAL colours available on request .																
HID 6195-150G12																	
	Albano	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6125-70</td><td rowspan="2">Albano is manufactured in extruded aluminium with an organically shaped column with internal anti-glare aluminum louvre . All hardware is of stainless steel with silicon gaskets. Luminaire complies IP66 protection class.Luminare is available in 3.5m height and upto 150w HID lamp.</td></tr><tr><td>HID 6125-150</td></tr></table>	Model No		HID 6125-70	Albano is manufactured in extruded aluminium with an organically shaped column with internal anti-glare aluminum louvre . All hardware is of stainless steel with silicon gaskets. Luminaire complies IP66 protection class.Luminare is available in 3.5m height and upto 150w HID lamp.	HID 6125-150										
Model No																	
HID 6125-70	Albano is manufactured in extruded aluminium with an organically shaped column with internal anti-glare aluminum louvre . All hardware is of stainless steel with silicon gaskets. Luminaire complies IP66 protection class.Luminare is available in 3.5m height and upto 150w HID lamp.																
HID 6125-150																	
	Neero	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6115 -35AL</td><td rowspan="16">Neero bollards are designed to provide quality and performance offering the following features: Lighting performance; high lighting levels, glare control, zero upward light pollution and high uniformity. Style and engineering performance; robust design and construction, functional with clean and simple lines, discreet blending with surroundings. Quality materials; available in extruded aluminium, strong impact resistant UV stabilized clear polycarbonate lamp cover. Variety and options; supplied in 800mm standard height extruded aluminium polyester painted in a choice of colours, variety of light sources and optics, range of accessories. A high performing adaptable product suitable for a variety of installations, Landscape, public and pedestrian areas.</td></tr><tr><td>HID 6115-70AL</td></tr><tr><td>HID 6115-35DL</td></tr><tr><td>HID 6115-70DL</td></tr><tr><td>HID 6115-35PC</td></tr><tr><td>HID 6115-70-PC</td></tr><tr><td>HID 6116-35AL</td></tr><tr><td>HID 6116-70AL</td></tr><tr><td>HID 6116-35DL</td></tr><tr><td>HID 6116-70DL</td></tr><tr><td>HID 6116-35PC</td></tr><tr><td>HID 6116-70-PC</td></tr></table>	Model No		HID 6115 -35AL	Neero bollards are designed to provide quality and performance offering the following features: Lighting performance; high lighting levels, glare control, zero upward light pollution and high uniformity. Style and engineering performance; robust design and construction, functional with clean and simple lines, discreet blending with surroundings. Quality materials; available in extruded aluminium, strong impact resistant UV stabilized clear polycarbonate lamp cover. Variety and options; supplied in 800mm standard height extruded aluminium polyester painted in a choice of colours, variety of light sources and optics, range of accessories. A high performing adaptable product suitable for a variety of installations, Landscape, public and pedestrian areas.	HID 6115-70AL	HID 6115-35DL	HID 6115-70DL	HID 6115-35PC	HID 6115-70-PC	HID 6116-35AL	HID 6116-70AL	HID 6116-35DL	HID 6116-70DL	HID 6116-35PC	HID 6116-70-PC
Model No																	
HID 6115 -35AL	Neero bollards are designed to provide quality and performance offering the following features: Lighting performance; high lighting levels, glare control, zero upward light pollution and high uniformity. Style and engineering performance; robust design and construction, functional with clean and simple lines, discreet blending with surroundings. Quality materials; available in extruded aluminium, strong impact resistant UV stabilized clear polycarbonate lamp cover. Variety and options; supplied in 800mm standard height extruded aluminium polyester painted in a choice of colours, variety of light sources and optics, range of accessories. A high performing adaptable product suitable for a variety of installations, Landscape, public and pedestrian areas.																
HID 6115-70AL																	
HID 6115-35DL																	
HID 6115-70DL																	
HID 6115-35PC																	
HID 6115-70-PC																	
HID 6116-35AL																	
HID 6116-70AL																	
HID 6116-35DL																	
HID 6116-70DL																	
HID 6116-35PC																	
HID 6116-70-PC																	
		Albano Jr	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6161-35</td><td rowspan="2">Albano is manufactured in extruded aluminium with an organically shaped column with internal anti-glare aluminum louvre . All hardware is of stainless steel with silicon gaskets. Luminaire complies IP66 protection class. Available in 1230mm height and upto 70w HID .</td></tr><tr><td>HID 6161-70</td></tr></table>	Model No			HID 6161-35	Albano is manufactured in extruded aluminium with an organically shaped column with internal anti-glare aluminum louvre . All hardware is of stainless steel with silicon gaskets. Luminaire complies IP66 protection class. Available in 1230mm height and upto 70w HID .	HID 6161-70								
Model No																	
HID 6161-35		Albano is manufactured in extruded aluminium with an organically shaped column with internal anti-glare aluminum louvre . All hardware is of stainless steel with silicon gaskets. Luminaire complies IP66 protection class. Available in 1230mm height and upto 70w HID .															
HID 6161-70																	



Trapez

Model No

HID 6126-20 PGJ5

HID 6126-70 G12

Trapez is made of extruded aluminium high resistance to oxidation, aluminum louvres, with vandal proof polycarbonate diffuser and tainless steel fixings. Available in 785mm height and suitable for 20w and 70w HID lamps .



Riviera

Model No

HID 6144-1000- FL-SY-E40/DE

HID 6144 1000-FL-ASY-E40/DE

HID 6144-1000-BM-SY-E40/DE

HID 6144-1000-BM-ASY-E40/DE

HID 6144-2000-FL-SY-E40/DE

HID 6144-2000-FL-ASY-E40/DE

HID-6144-2000-BM-SY-E40/DE

HID 6144-2000-BM-ASY-E40/DE

Riviera is a range of 1000W and 2000W Symmetrical / asymmetrical high performance floodlights designed for indoor and outdoor sports lighting applications. Body in die-cast aluminium finished polyester powder coated. Cover fixing clips in stainless steel with safety hook. Ignitor housing complete with ignitor mounted directly to body. Reflectors in high purity aluminium. Beam optics available in DE/E40 lamp holder in symmetric/asymmetric options , 1000w /2000w . Flood optics available in DE/E40 lamp holder in symmetric/asymmetric options, 1000w / 2000w .



Challenger

Model No

HID 6157-1000NB/MB/WB

HID 6157-2000NB/MB/WB

Challenger is aluminum pressure die cast body in three alternative reflector versions is designed to provide highly efficient illumination of larger areas with 1kW and 2kW lamps. The floodlight is particularly suitable for lighting sports complexes & airports areas .



Pinguino & Pinguino Nano

Model No

HID 6113-70 Pinguino Nano

HID 6113-150 Pinguino Nano

HID 6114-250 Pinguino

HID 6114-400 Pinguino

Die-cast aluminium body with wide cooling fins. . Steel support bracket. Polyester powder paint resistant to corrosion, Thermal-shock resistant tempered glass diffuser. Corrected wiring on removable zinc-plated steel plate. Stainless steel external clamps . Two models available one with 70/150w and second with 250/400w HID lamp..



Tornado

Model No

HID 6121-70NB/MB

HID 6122-150NB/MB/BW

HID 6122-250NB/MB/BW

HID 6123-400NB/MB/BW








HID 6123-1000NB/MB

Tornado is a powerful beam luminaire for use as facade lighting, pile lighting, bridge lighting or for creating accent at public place. Non Integral with separate gearbox Luminaire is available from 70w till 1000w lamps. The unique design is made of aluminum die cast with pure aluminum reflectors, Tempered glass, silicon gaskets and stainless steel hardware. Options: Narrow Beam, Medium beam and Batwing optics available.

	Torch	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6135-35 G12</td><td rowspan="5">A compact optical body available in two sizes make Torch a flexible solution to suit the most different project requirements. Made of pressure die cast aluminum housing with tempered glass , silicon gaskets and stainless steel hardware. Luminaire is available in symmetric/asymmetric and beam optics or with Glare Control version.</td></tr><tr><td>HID 6136-70 DE -SY/ASY</td></tr><tr><td>HID 6136 150 DE -SY/ASY</td></tr><tr><td>HID 6136-70G12 BM/GC</td></tr><tr><td>HID 6136-150G12 -BM/GC</td></tr></table>	Model No		HID 6135-35 G12	A compact optical body available in two sizes make Torch a flexible solution to suit the most different project requirements. Made of pressure die cast aluminum housing with tempered glass , silicon gaskets and stainless steel hardware. Luminaire is available in symmetric/asymmetric and beam optics or with Glare Control version.	HID 6136-70 DE -SY/ASY	HID 6136 150 DE -SY/ASY	HID 6136-70G12 BM/GC	HID 6136-150G12 -BM/GC
Model No										
HID 6135-35 G12	A compact optical body available in two sizes make Torch a flexible solution to suit the most different project requirements. Made of pressure die cast aluminum housing with tempered glass , silicon gaskets and stainless steel hardware. Luminaire is available in symmetric/asymmetric and beam optics or with Glare Control version.									
HID 6136-70 DE -SY/ASY										
HID 6136 150 DE -SY/ASY										
HID 6136-70G12 BM/GC										
HID 6136-150G12 -BM/GC										
	Beamer	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6124-70FX</td><td rowspan="4">Beamer luminaire is constructed from high quality die cast aluminium .Technopolymer outer recessing enclosure provides high corrosion resistance and strength. Toughened safety clear float glass IK10 (21Joule). Heat resistant silicone gaskets, to ensure a maintained IP67 seal. Many accent creating and glare control accessories available .</td></tr><tr><td>HID 6124-150FX</td></tr><tr><td>HID 6124-70AJ</td></tr><tr><td>HID 6124-150AJ</td></tr></table>	Model No		HID 6124-70FX	Beamer luminaire is constructed from high quality die cast aluminium .Technopolymer outer recessing enclosure provides high corrosion resistance and strength. Toughened safety clear float glass IK10 (21Joule). Heat resistant silicone gaskets, to ensure a maintained IP67 seal. Many accent creating and glare control accessories available .	HID 6124-150FX	HID 6124-70AJ	HID 6124-150AJ	
Model No										
HID 6124-70FX	Beamer luminaire is constructed from high quality die cast aluminium .Technopolymer outer recessing enclosure provides high corrosion resistance and strength. Toughened safety clear float glass IK10 (21Joule). Heat resistant silicone gaskets, to ensure a maintained IP67 seal. Many accent creating and glare control accessories available .									
HID 6124-150FX										
HID 6124-70AJ										
HID 6124-150AJ										
	Trendo	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6127-2X20 -PGj5</td><td rowspan="2">Triangular shape wall mounted up and down light in die cast and extruded aluminium fixture with tempered glass. Available in two models to answer all lighting design needs.</td></tr><tr><td>HID 6128-20 -PGj5</td></tr></table>	Model No		HID 6127-2X20 -PGj5	Triangular shape wall mounted up and down light in die cast and extruded aluminium fixture with tempered glass. Available in two models to answer all lighting design needs.	HID 6128-20 -PGj5			
Model No										
HID 6127-2X20 -PGj5	Triangular shape wall mounted up and down light in die cast and extruded aluminium fixture with tempered glass. Available in two models to answer all lighting design needs.									
HID 6128-20 -PGj5										
	Cendo	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6118-2x70-G12</td><td rowspan="2">Cendo HID is defined by its simplistic styling. Two sizes are available to meet diverse proportional requirements. The Extrusion aluminum housing with die cast end covers support the flat tempered glass lens. Asymmetrical reflectors provides added light control.</td></tr><tr><td>HID 6119-2x150-PAR38</td></tr></table>	Model No		HID 6118-2x70-G12	Cendo HID is defined by its simplistic styling. Two sizes are available to meet diverse proportional requirements. The Extrusion aluminum housing with die cast end covers support the flat tempered glass lens. Asymmetrical reflectors provides added light control.	HID 6119-2x150-PAR38			
Model No										
HID 6118-2x70-G12	Cendo HID is defined by its simplistic styling. Two sizes are available to meet diverse proportional requirements. The Extrusion aluminum housing with die cast end covers support the flat tempered glass lens. Asymmetrical reflectors provides added light control.									
HID 6119-2x150-PAR38										
	Cendo Ceiling	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6150-35-G12</td><td rowspan="4">Surface mounted luminaires distinguishes through a minimal mounting effort.Housing made of extruded aluminium, powder coated, Supporting ring made of die cast aluminum , front glass and highly polished reflector. Available in 35w /20w/70w & 150w .</td></tr><tr><td>HID 6150-20PLC -E27</td></tr><tr><td>HID 6151-70</td></tr><tr><td>HID 6151-150</td></tr></table>	Model No		HID 6150-35-G12	Surface mounted luminaires distinguishes through a minimal mounting effort.Housing made of extruded aluminium, powder coated, Supporting ring made of die cast aluminum , front glass and highly polished reflector. Available in 35w /20w/70w & 150w .	HID 6150-20PLC -E27	HID 6151-70	HID 6151-150	
Model No										
HID 6150-35-G12	Surface mounted luminaires distinguishes through a minimal mounting effort.Housing made of extruded aluminium, powder coated, Supporting ring made of die cast aluminum , front glass and highly polished reflector. Available in 35w /20w/70w & 150w .									
HID 6150-20PLC -E27										
HID 6151-70										
HID 6151-150										
	LukLite	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6120-70</td><td rowspan="3">Contemporary wall mounted luminaire adds visual structure to a simple form. Trans-lucent tempered glass provides soft symmetrical distribution. Fixture is made of die cast aluminum with all hardware is stainless steel. Available upto 70w HID.</td></tr><tr><td>HID 6120-42 CFL EB</td></tr><tr><td>HID 6120-42 CFL MB</td></tr></table>	Model No		HID 6120-70	Contemporary wall mounted luminaire adds visual structure to a simple form. Trans-lucent tempered glass provides soft symmetrical distribution. Fixture is made of die cast aluminum with all hardware is stainless steel. Available upto 70w HID.	HID 6120-42 CFL EB	HID 6120-42 CFL MB		
Model No										
HID 6120-70	Contemporary wall mounted luminaire adds visual structure to a simple form. Trans-lucent tempered glass provides soft symmetrical distribution. Fixture is made of die cast aluminum with all hardware is stainless steel. Available upto 70w HID.									
HID 6120-42 CFL EB										
HID 6120-42 CFL MB										

	WallPak	<table><tr><th>Model No</th><th></th></tr><tr><td>HID 6131-70</td><td rowspan="4">Wallpak family compises of four models suitable to fullfil every need of lighting requirements of Indusrtly, commercial or residential security. Made of pressure die cast with high im-pact borosilicate glass (PC in 70w models) lens , pure silicon gaskets, stainless steel hardware and powder coated, fixtures offer the utmost quality to the user.</td></tr><tr><td>HID 6132-150</td></tr><tr><td>HID 6133-250</td></tr><tr><td>HID 6134-400</td></tr></table>	Model No		HID 6131-70	Wallpak family compises of four models suitable to fullfil every need of lighting requirements of Indusrtly, commercial or residential security. Made of pressure die cast with high im-pact borosilicate glass (PC in 70w models) lens , pure silicon gaskets, stainless steel hardware and powder coated, fixtures offer the utmost quality to the user.	HID 6132-150	HID 6133-250	HID 6134-400		
Model No											
HID 6131-70	Wallpak family compises of four models suitable to fullfil every need of lighting requirements of Indusrtly, commercial or residential security. Made of pressure die cast with high im-pact borosilicate glass (PC in 70w models) lens , pure silicon gaskets, stainless steel hardware and powder coated, fixtures offer the utmost quality to the user.										
HID 6132-150											
HID 6133-250											
HID 6134-400											
	Orbit	<table><tr><th>Model No</th><th></th></tr><tr><td>HID 6158-35 G12</td><td rowspan="5">Orbit the answer to lighting requirements in modern retails, trade fair pavilions, shopping centres, foyers, corridors and warehouse lighting. Housing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically polished and anodised.The toughened front glass is clamped to achieve IP65 protection. Plain or facetted aluminum reflectors or acrylic decoraive refractors are available in various diameters .</td></tr><tr><td>HID 6158-70</td></tr><tr><td>HID 6159-150</td></tr><tr><td>HID 6160-250</td></tr><tr><td>HID 6160-400</td></tr></table>	Model No		HID 6158-35 G12	Orbit the answer to lighting requirements in modern retails, trade fair pavilions, shopping centres, foyers, corridors and warehouse lighting. Housing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically polished and anodised.The toughened front glass is clamped to achieve IP65 protection. Plain or facetted aluminum reflectors or acrylic decoraive refractors are available in various diameters .	HID 6158-70	HID 6159-150	HID 6160-250	HID 6160-400	
Model No											
HID 6158-35 G12	Orbit the answer to lighting requirements in modern retails, trade fair pavilions, shopping centres, foyers, corridors and warehouse lighting. Housing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically polished and anodised.The toughened front glass is clamped to achieve IP65 protection. Plain or facetted aluminum reflectors or acrylic decoraive refractors are available in various diameters .										
HID 6158-70											
HID 6159-150											
HID 6160-250											
HID 6160-400											
	Muna	<table><tr><th>Model No</th><th></th></tr><tr><td>HID 6142-70</td><td rowspan="6">Sololuce high bay fixtures enhance light quality and provide energyefficient alternatives to traditional HID fixtures. Two different types of Sololuce high bay fixtures are available , Muna and Muna + . Housing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically polished and anodised. The toughened front glass is clamped into the aluminium bezel. Fully integral control gear.Plain or facetted aluminum re-flectors or acrylic decorative refractors are available in various diameters.</td></tr><tr><td>HID 6142-150</td></tr><tr><td>HID 6142-250</td></tr><tr><td>HID 6142-400</td></tr><tr><td>HID 6143-250</td></tr><tr><td>HID 6143-400</td></tr></table>	Model No		HID 6142-70	Sololuce high bay fixtures enhance light quality and provide energyefficient alternatives to traditional HID fixtures. Two different types of Sololuce high bay fixtures are available , Muna and Muna + . Housing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically polished and anodised. The toughened front glass is clamped into the aluminium bezel. Fully integral control gear.Plain or facetted aluminum re-flectors or acrylic decorative refractors are available in various diameters.	HID 6142-150	HID 6142-250	HID 6142-400	HID 6143-250	HID 6143-400
Model No											
HID 6142-70	Sololuce high bay fixtures enhance light quality and provide energyefficient alternatives to traditional HID fixtures. Two different types of Sololuce high bay fixtures are available , Muna and Muna + . Housing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically polished and anodised. The toughened front glass is clamped into the aluminium bezel. Fully integral control gear.Plain or facetted aluminum re-flectors or acrylic decorative refractors are available in various diameters.										
HID 6142-150											
HID 6142-250											
HID 6142-400											
HID 6143-250											
HID 6143-400											
	Impact	<table><tr><th>Model No</th><th></th></tr><tr><td>HID 6155-150</td><td rowspan="3">Housing made of die-cast aluminium. Strengthened main re-flector made of 99.98% pure aluminium , toughened front glass is clamped to achieve IP65 protection. Plain or fac-etted aluminum reflectors or acrylic decorative refractors are available in various diameters .</td></tr><tr><td>HID 6155-250</td></tr><tr><td>HID 6155-400</td></tr></table>	Model No		HID 6155-150	Housing made of die-cast aluminium. Strengthened main re-flector made of 99.98% pure aluminium , toughened front glass is clamped to achieve IP65 protection. Plain or fac-etted aluminum reflectors or acrylic decorative refractors are available in various diameters .	HID 6155-250	HID 6155-400			
Model No											
HID 6155-150	Housing made of die-cast aluminium. Strengthened main re-flector made of 99.98% pure aluminium , toughened front glass is clamped to achieve IP65 protection. Plain or fac-etted aluminum reflectors or acrylic decorative refractors are available in various diameters .										
HID 6155-250											
HID 6155-400											
	Milano	<table><tr><th>Model No</th><th></th></tr><tr><td>HID 6156-70</td><td rowspan="3">Pendant lighting fixture suitable for illumination of working surfaces , Hypermarkets ,and indoor spaces in general. Hous-ing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically Matt polished and anodised.</td></tr><tr><td>HID 6156-150</td></tr><tr><td>HID 6156-250</td></tr></table>	Model No		HID 6156-70	Pendant lighting fixture suitable for illumination of working surfaces , Hypermarkets ,and indoor spaces in general. Hous-ing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically Matt polished and anodised.	HID 6156-150	HID 6156-250			
Model No											
HID 6156-70	Pendant lighting fixture suitable for illumination of working surfaces , Hypermarkets ,and indoor spaces in general. Hous-ing incorporating cooling fins, made of die-cast aluminium. Strengthened main reflector made of 99.98% pure aluminium, chemically Matt polished and anodised.										
HID 6156-150											
HID 6156-250											
	Notte	<table><tr><th>Model No</th><th></th></tr><tr><td>HID 6190-70</td><td>Notte stands for modern luminaire design for shopping cen-tres and exhibition spaces, representative public buildings, airports, hotels and restaurants. Housing is made of heat dis-sipating cooling fins made of aluminum extrusion profile, alu-minum reflector with frosted drop glass</td></tr></table>	Model No		HID 6190-70	Notte stands for modern luminaire design for shopping cen-tres and exhibition spaces, representative public buildings, airports, hotels and restaurants. Housing is made of heat dis-sipating cooling fins made of aluminum extrusion profile, alu-minum reflector with frosted drop glass					
Model No											
HID 6190-70	Notte stands for modern luminaire design for shopping cen-tres and exhibition spaces, representative public buildings, airports, hotels and restaurants. Housing is made of heat dis-sipating cooling fins made of aluminum extrusion profile, alu-minum reflector with frosted drop glass										

	Tiara	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6191-70</td><td>The exceptional aesthetics of this luminaire is one persuasive factor; the technology that combines decades of Sololuce experience with the highest quality standards is another. Housing is made of heat dissipating cooling fins made of die cast aluminum, aluminum reflector with front glass</td></tr></table>	Model No		HID 6191-70	The exceptional aesthetics of this luminaire is one persuasive factor; the technology that combines decades of Sololuce experience with the highest quality standards is another. Housing is made of heat dissipating cooling fins made of die cast aluminum, aluminum reflector with front glass		
Model No								
HID 6191-70	The exceptional aesthetics of this luminaire is one persuasive factor; the technology that combines decades of Sololuce experience with the highest quality standards is another. Housing is made of heat dissipating cooling fins made of die cast aluminum, aluminum reflector with front glass							
	Interics	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6185-20/G8.5</td><td rowspan="3">Interics is a tough luminaire with IP66 protection class for outdoor ceiling application. It is made with high quality corrosion resistant pressure die cast aluminum, with high performance optics for use with a variety of light sources. Stainless steel frame in 316 SS or Die casting aluminium frame</td></tr><tr><td>HID 6185-35/G12</td></tr><tr><td>HID 6185-50/G12</td></tr></table>	Model No		HID 6185-20/G8.5	Interics is a tough luminaire with IP66 protection class for outdoor ceiling application. It is made with high quality corrosion resistant pressure die cast aluminum, with high performance optics for use with a variety of light sources. Stainless steel frame in 316 SS or Die casting aluminium frame	HID 6185-35/G12	HID 6185-50/G12
Model No								
HID 6185-20/G8.5	Interics is a tough luminaire with IP66 protection class for outdoor ceiling application. It is made with high quality corrosion resistant pressure die cast aluminum, with high performance optics for use with a variety of light sources. Stainless steel frame in 316 SS or Die casting aluminium frame							
HID 6185-35/G12								
HID 6185-50/G12								
	Ace	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6178-35-G12</td><td rowspan="2">Ace is designed for 70w metal halide lamp for shops, restaurants, hotels, galleries, exhibitions halls and museums . Specially designed aluminum die cast fins keeps the temperature of metal halide within required parameters and hence avoids colour shift .</td></tr><tr><td>HID 6178-70-G12</td></tr></table>	Model No		HID 6178-35-G12	Ace is designed for 70w metal halide lamp for shops, restaurants, hotels, galleries, exhibitions halls and museums . Specially designed aluminum die cast fins keeps the temperature of metal halide within required parameters and hence avoids colour shift .	HID 6178-70-G12	
Model No								
HID 6178-35-G12	Ace is designed for 70w metal halide lamp for shops, restaurants, hotels, galleries, exhibitions halls and museums . Specially designed aluminum die cast fins keeps the temperature of metal halide within required parameters and hence avoids colour shift .							
HID 6178-70-G12								
	Mobile	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6179-70-G12</td><td rowspan="2">Mobile is designed for 70w/150w metal halide lamp for shops, restaurants, hotels, galleries, exhibitions halls and museums . Fixture has 3mm thick tempered front glass & adjustable head in IP20 protection class and comes in white , black and grey as standard finishes.</td></tr><tr><td>HID 6179-150-G12</td></tr></table>	Model No		HID 6179-70-G12	Mobile is designed for 70w/150w metal halide lamp for shops, restaurants, hotels, galleries, exhibitions halls and museums . Fixture has 3mm thick tempered front glass & adjustable head in IP20 protection class and comes in white , black and grey as standard finishes.	HID 6179-150-G12	
Model No								
HID 6179-70-G12	Mobile is designed for 70w/150w metal halide lamp for shops, restaurants, hotels, galleries, exhibitions halls and museums . Fixture has 3mm thick tempered front glass & adjustable head in IP20 protection class and comes in white , black and grey as standard finishes.							
HID 6179-150-G12								
	Kevi	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6180-35-G12</td><td rowspan="2">Kevi is a round head metal halide luminaire suitable for accepting 35w and 70w G12 MH Lamp . Fixture comes with adjustable head in IP20 ingress protection and in white , black and grey as standard finishes.</td></tr><tr><td>HID 6180-70-G12</td></tr></table>	Model No		HID 6180-35-G12	Kevi is a round head metal halide luminaire suitable for accepting 35w and 70w G12 MH Lamp . Fixture comes with adjustable head in IP20 ingress protection and in white , black and grey as standard finishes.	HID 6180-70-G12	
Model No								
HID 6180-35-G12	Kevi is a round head metal halide luminaire suitable for accepting 35w and 70w G12 MH Lamp . Fixture comes with adjustable head in IP20 ingress protection and in white , black and grey as standard finishes.							
HID 6180-70-G12								
	Kris	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6181-35-G12</td><td rowspan="2">Kris is a square head metal halide luminaire suitable for accepting 35w and 70w G12 MH Lamp. Fixture comes with adjustable head in IP20 ingress protection and in white , black and grey as standard finishes</td></tr><tr><td>HID 6181-70-G12</td></tr></table>	Model No		HID 6181-35-G12	Kris is a square head metal halide luminaire suitable for accepting 35w and 70w G12 MH Lamp. Fixture comes with adjustable head in IP20 ingress protection and in white , black and grey as standard finishes	HID 6181-70-G12	
Model No								
HID 6181-35-G12	Kris is a square head metal halide luminaire suitable for accepting 35w and 70w G12 MH Lamp. Fixture comes with adjustable head in IP20 ingress protection and in white , black and grey as standard finishes							
HID 6181-70-G12								
	Siena	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6182-120-GU5.3/GU10</td><td rowspan="3">Siena has been designed with light source place deep inside to create an accent lighting but without glare. This fixture is suitable to illuminate shops, restaurants, hotels, and especially galleries, exhibitions and museums. Siena support MR16 in GU5.3 and GU10 base halogen lamps</td></tr><tr><td>HID 6182-135-GU5.3/GU10</td></tr><tr><td>HID 6182-150-GU5.5/GU10</td></tr></table>	Model No		HID 6182-120-GU5.3/GU10	Siena has been designed with light source place deep inside to create an accent lighting but without glare. This fixture is suitable to illuminate shops, restaurants, hotels, and especially galleries, exhibitions and museums. Siena support MR16 in GU5.3 and GU10 base halogen lamps	HID 6182-135-GU5.3/GU10	HID 6182-150-GU5.5/GU10
Model No								
HID 6182-120-GU5.3/GU10	Siena has been designed with light source place deep inside to create an accent lighting but without glare. This fixture is suitable to illuminate shops, restaurants, hotels, and especially galleries, exhibitions and museums. Siena support MR16 in GU5.3 and GU10 base halogen lamps							
HID 6182-135-GU5.3/GU10								
HID 6182-150-GU5.5/GU10								

	Alicia Nano	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6177-120-GU5.3/GU10</td><td rowspan="3">Alicia Nano has been designed with invisible, adjustable lamp head in CRCA powder coated body which support MR16 in GU5.3 and GU10 base halogen lamps</td></tr><tr><td>HID 6177-135-GU5.3/GU10</td></tr><tr><td>HID 6177-150-GU5.5/GU10</td></tr></table>	Model No		HID 6177-120-GU5.3/GU10	Alicia Nano has been designed with invisible, adjustable lamp head in CRCA powder coated body which support MR16 in GU5.3 and GU10 base halogen lamps	HID 6177-135-GU5.3/GU10	HID 6177-150-GU5.5/GU10
Model No								
HID 6177-120-GU5.3/GU10	Alicia Nano has been designed with invisible, adjustable lamp head in CRCA powder coated body which support MR16 in GU5.3 and GU10 base halogen lamps							
HID 6177-135-GU5.3/GU10								
HID 6177-150-GU5.5/GU10								
	Aqua	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6176-120-GU5.3/GU10</td><td rowspan="3">Aqua has been specially designed downlight with finned die cast aluminum body with fixed head which support MR16 in GU5.3 and GU10 base halogen lamps</td></tr><tr><td>HID 6176-135-GU5.3/GU10</td></tr><tr><td>HID 6176-150-GU5.5/GU10</td></tr></table>	Model No		HID 6176-120-GU5.3/GU10	Aqua has been specially designed downlight with finned die cast aluminum body with fixed head which support MR16 in GU5.3 and GU10 base halogen lamps	HID 6176-135-GU5.3/GU10	HID 6176-150-GU5.5/GU10
Model No								
HID 6176-120-GU5.3/GU10	Aqua has been specially designed downlight with finned die cast aluminum body with fixed head which support MR16 in GU5.3 and GU10 base halogen lamps							
HID 6176-135-GU5.3/GU10								
HID 6176-150-GU5.5/GU10								
	Volo	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6172-120-GU5.3/GU10</td><td rowspan="3">Volo is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps</td></tr><tr><td>HID 6172-135-GU5.3/GU10</td></tr><tr><td>HID 6172-150-GU5.5/GU10</td></tr></table>	Model No		HID 6172-120-GU5.3/GU10	Volo is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps	HID 6172-135-GU5.3/GU10	HID 6172-150-GU5.5/GU10
Model No								
HID 6172-120-GU5.3/GU10	Volo is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps							
HID 6172-135-GU5.3/GU10								
HID 6172-150-GU5.5/GU10								
	Capri	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6173-120-GU5.3/GU10</td><td rowspan="3">Capri is drop glass construction downlight which support MR16 in GU5.3 and GU10 base halogen lamps</td></tr><tr><td>HID 6173-135-GU5.3/GU10</td></tr><tr><td>HID 6173-150-GU5.5/GU10</td></tr></table>	Model No		HID 6173-120-GU5.3/GU10	Capri is drop glass construction downlight which support MR16 in GU5.3 and GU10 base halogen lamps	HID 6173-135-GU5.3/GU10	HID 6173-150-GU5.5/GU10
Model No								
HID 6173-120-GU5.3/GU10	Capri is drop glass construction downlight which support MR16 in GU5.3 and GU10 base halogen lamps							
HID 6173-135-GU5.3/GU10								
HID 6173-150-GU5.5/GU10								
	Vista	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6174-120-GU5.3/GU10</td><td rowspan="3">Vista is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps</td></tr><tr><td>HID 6174-135-GU5.3/GU10</td></tr><tr><td>HID 6174-150-GU5.5/GU10</td></tr></table>	Model No		HID 6174-120-GU5.3/GU10	Vista is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps	HID 6174-135-GU5.3/GU10	HID 6174-150-GU5.5/GU10
Model No								
HID 6174-120-GU5.3/GU10	Vista is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps							
HID 6174-135-GU5.3/GU10								
HID 6174-150-GU5.5/GU10								
	Corona	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6171-120-GU5.3/GU10</td><td rowspan="3">Corona is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps</td></tr><tr><td>HID 6171-135-GU5.3/GU10</td></tr><tr><td>HID 6171-150-GU5.5/GU10</td></tr></table>	Model No		HID 6171-120-GU5.3/GU10	Corona is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps	HID 6171-135-GU5.3/GU10	HID 6171-150-GU5.5/GU10
Model No								
HID 6171-120-GU5.3/GU10	Corona is an IP65 downlight which support MR16 in GU5.3 and GU10 base halogen lamps							
HID 6171-135-GU5.3/GU10								
HID 6171-150-GU5.5/GU10								
	Mobile Nano	<table><tr><th colspan="2">Model No</th></tr><tr><td>HID 6175-120-GU5.3/GU10</td><td rowspan="3">Mobile Nano is an IP20 downlight which support MR16 in GU5.3 and GU10 base halogen lamps</td></tr><tr><td>HID 6175-135-GU5.3/GU10</td></tr><tr><td>HID 6175-150-GU5.5/GU10</td></tr></table>	Model No		HID 6175-120-GU5.3/GU10	Mobile Nano is an IP20 downlight which support MR16 in GU5.3 and GU10 base halogen lamps	HID 6175-135-GU5.3/GU10	HID 6175-150-GU5.5/GU10
Model No								
HID 6175-120-GU5.3/GU10	Mobile Nano is an IP20 downlight which support MR16 in GU5.3 and GU10 base halogen lamps							
HID 6175-135-GU5.3/GU10								
HID 6175-150-GU5.5/GU10								

Sololuce Lighting - Terms and Conditions of Sale

Effective January 1st, 2013

Applicability of these Terms

1. Except as expressly agreed in writing signed by a member of the Sololuce management, the present Terms and Conditions shall constitute the entire sales agreement between Sololuce and the Customer. Any contrary or additional terms or conditions submitted by the Customer (other than the description of the products being ordered and the requested quantities, price, shipping date, and shipping location contained in Customer's purchase order) shall be deemed to be of no force order shall indicate Customer's acknowledgement of and agreement with the present Terms and Conditions.

2. Sololuce reserves the right to change these Terms and Conditions without notice. Prices, Specifications and Quotations

1. All prices are subject to change without notice.

2. Prices exclude all taxes.

3. Specifications are subject to change without notice. Consult factory for verification. The compliance of our product to individual project specifications and the approval for their use is not warranted by Sololuce.

4. All quotations, bids, contracts and orders are subject to the final written approval, acceptance and/or confirmation of Sololuce. Quotations will be valid for a period of thirty (30) days counting from the date of the quotation. Confirmed prices on deferred or hold orders will be valid for ninety (90) days.

Intellectual Property

Sololuce remains the sole owner of the integrality of intellectual property rights on all plans, drawings, studies and any other documents distributed by Sololuce, as well as the integral rights on the technologies and know-how related to the Sololuce products.

Orders

1. The minimum acceptable order is \$300 book price, with the exception of orders for replacement parts which carry a \$100 minimum.

2. Delivery times communicated by Sololuce are estimates only and do not give rise to any further commitment from Sololuce.

Freight

1. All orders having a distributor price exceeding \$5,000 for one destination for one shipment are shipped F.O.B. factory with freight prepaid and allowed to the nearest destination served by a common carrier (off loading not included) within UAE. All orders having a distributor price of less than \$5,000 for one destination for one shipment will be assessed freight and handling charges.

2. For orders that qualify for freight allowance, routing and mode of transportation are determined by Sololuce, unless otherwise specified and requested by the Customer, in which case the Customer assumes any or all additional charges.

3. Shipment must be unloaded promptly as Sololuce will pay no demurrage.

4. All claims for damage to or loss of any goods in transit shall be made by Customer with delivering carrier.

Payment Terms

1. All orders are accepted with 30% advance and balance before dispatch from factory. Irrevocable, unconditional L/C is accepted in lieu of balance payment before dispatch.

2. 1,5% monthly interest charge will apply to all past due accounts.

Order Changes

1. An order change fee will apply in case of any product modification, change in quantity or any other change in the order after this order has been released and scheduled. This fee will be determined at Sololuce's discretion.

2. Any change order will automatically involve a reschedule of the shipment date.

Cancellations

1. All cancelled orders are subject to a cancellation charge to be determined at Sololuce's discretion, on the basis of the costs Sololuce already incurred for the order at the moment of cancellation.

2. Partial cancellations may affect freight prepayments, whereas additions to orders which have already been processed will be considered separate orders for purposes of freight prepayment.

Returns

1. No product(s) will be accepted for return unless accompanied by a Return Goods Authorization issued by the Sololuce Sales Coordinator only. Requests to return merchandise must be made within three (3) months of the date of shipment by Sololuce. A restocking and reworking charge covering all costs, including two-way freight, will apply to all returns. All returned products must be in salable condition in order to qualify for credit.

2. Orders accepted by Sololuce for customized, modified or specifically produced items are non-cancelable and said items are non-returnable.

Limited Warranty

1. It is the Customer's responsibility to inspect the merchandise upon delivery and before installation, and report any error or defect to Sololuce, in writing, within ten (10) days of said delivery. Should the Customer fail to do so, all parties will conclude that the merchandise has been delivered in accordance with the order.

2. Sololuce warrants all products sold hereunder to be free from defect in manufacturing, under normal and proper storage, installation, and use, for a period of one (1) year from the date of shipment. This warranty liability any parts recognized by Sololuce as being defective. Sololuce will only be liable when Customer proves that the defect arose during the normal use of the product, and that it existed at the moment the product was shipped. Any and all other costs, including costs of labor, transport, or costs relating to the removal, installation or proper selection of products, are excluded from this warranty. SOLOLUCE HEREBY EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED.

3. The replacement of defective parts by Sololuce will not give the Customer any right to compensation of damages.

4. Parts or products not manufactured by Sololuce, such as LED lamps, driver, Fluorescent ballasts, H.I.D. ballasts and photoelectric controls, carry the original manufacturer's warranty.

5. Sololuce will not be liable for failure(s) or delay(s) in the execution of the order which are directly or indirectly caused by war, conditions of war, enemy actions, national emergency, sabotage, revolution or other disorders, inadequate transportation facilities, inability to secure raw materials or supplies, fuel, or power, fire, flood, windstorm, or other acts of nature, strikes, lockouts, or other labor disturbances, orders or acts of any authority, or any cause of similar or different kind which is beyond the reasonable control of Sololuce.

6. In no event shall Sololuce be liable for any damage occurred as a result of the installation of damaged goods. Applicable law and Courts The sales agreement between Sololuce and the Customer shall be deemed to have been made and accepted in territory of Dubai, UAE, and shall be governed by the laws of the UAE. All disputes arising from or related to present agreement